

EXHIBIT D



US008454116B2

(12) **United States Patent**
Asauchi

(10) **Patent No.:** **US 8,454,116 B2**
(45) **Date of Patent:** **Jun. 4, 2013**

(54) **PRINTING MATERIAL CONTAINER, AND BOARD MOUNTED ON PRINTING MATERIAL CONTAINER**

(75) Inventor: **Noboru Asauchi**, Nagano (JP)

(73) Assignee: **Seiko Epson Corporation**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/608,658**

(22) Filed: **Sep. 10, 2012**

(65) **Prior Publication Data**

US 2013/0027483 A1 Jan. 31, 2013

Related U.S. Application Data

(63) Continuation of application No. 12/257,914, filed on Oct. 24, 2008, now Pat. No. 8,366,233, which is a continuation of application No. 12/040,308, filed on Feb. 29, 2008, now Pat. No. 7,484,825, which is a continuation of application No. 11/611,641, filed on Dec. 15, 2006, now Pat. No. 7,562,958.

(30) **Foreign Application Priority Data**

Dec. 26, 2005 (JP) 2005-372028
Aug. 11, 2006 (JP) 2006-220751

(51) **Int. Cl.**
B41J 2/16 (2006.01)

(52) **U.S. Cl.**
USPC **347/19; 347/50; 439/157; 439/534;**
439/924.1

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,683,481	A	7/1987	Johnson
4,739,352	A	4/1988	Gorelick et al.
5,032,855	A	7/1991	Taniguchi et al.
5,049,898	A	9/1991	Arthur et al.
5,278,584	A	1/1994	Keefe et al.
5,565,786	A	10/1996	Balousek
5,610,635	A	3/1997	Murray et al.
5,646,660	A	7/1997	Murray

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1272081	A	11/2000
CN	1532064	A	9/2004

(Continued)

OTHER PUBLICATIONS

Photos of HP No. 10 cartridge.

(Continued)


Primary Examiner — Michael Zarroli

(74) *Attorney, Agent, or Firm* — Stroock & Stroock & Lavan LLP

(57) **ABSTRACT**

A printing material container detachably attachable to a printing apparatus having apparatus-side terminals. The container can comprise an electrical device, a memory device and a plurality of terminals. First and second terminals can be coupled to the electrical device and a plurality of memory terminals can be coupled to the memory device. Terminal contact portions are present where the terminals contact a respective apparatus side contact forming member. A short detection contact portion can be positioned to contact a contact forming member that itself is coupled to a short detection circuit of the printing apparatus. The terminals can be arranged with the memory terminal contact portions located to the left of the second terminal contact portion and to the right of the first terminal contact portion. The contact portion that is second farthest to the right can be the third contact portion.

30 Claims, 22 Drawing Sheets



US 8,454,116 B2

Page 2

U.S. PATENT DOCUMENTS

5,699,091 A 12/1997 Bullock et al.
 5,710,582 A 1/1998 Hawkins et al.
 5,751,311 A 5/1998 Drake
 5,788,388 A 8/1998 Cowger et al.
 5,940,095 A 8/1999 Parish et al.
 6,039,428 A 3/2000 Juve
 6,086,193 A 7/2000 Shimada et al.
 6,130,695 A 10/2000 Childers et al.
 6,155,664 A 12/2000 Cook
 6,155,678 A 12/2000 Komplin et al.
 6,161,915 A 12/2000 Bolash et al.
 6,164,743 A 12/2000 Hmelar et al.
 6,260,942 B1 7/2001 Ahne et al.
 6,280,017 B1 8/2001 Miyauchi
 6,550,902 B2 4/2003 Shinada et al.
 6,585,359 B1 7/2003 Gasvoda et al.
 6,749,287 B2 6/2004 Osada et al.
 7,008,053 B2 3/2006 Hashii et al.
 7,175,244 B2 2/2007 Usui et al.
 7,201,463 B2 4/2007 Kosugi et al.
 7,219,985 B2 5/2007 Shinada et al.
 7,237,864 B2 7/2007 Sarmast et al.
 7,306,308 B2 12/2007 Tsukada
 2002/0003551 A1 1/2002 Beck et al.
 2002/0024559 A1 2/2002 Murray et al.
 2002/0135623 A1 9/2002 Tsukada et al.
 2002/0167574 A1 11/2002 Shinada et al.
 2002/0171700 A1 11/2002 Shinada et al.
 2002/0180823 A1 12/2002 Shinada et al.
 2003/0043216 A1 3/2003 Usui et al.
 2003/0054003 A1 3/2003 Leung et al.
 2003/0058296 A1 3/2003 Shinada et al.
 2003/0079655 A1 5/2003 Takahashi et al.
 2003/0085969 A1 5/2003 Shinada et al.
 2003/0137568 A1 7/2003 Shinada et al.
 2004/0155913 A1 8/2004 Kosugi et al.
 2005/0057622 A1 3/2005 Kimura et al.
 2005/0146576 A1 7/2005 Shinada et al.
 2005/0146579 A1 7/2005 Sasaki et al.
 2005/0195255 A1 9/2005 Shinada et al.
 2005/0219303 A1 10/2005 Matsumoto et al.
 2005/0237349 A1 10/2005 Nishihara
 2005/0270315 A1 12/2005 Yamamoto
 2006/0007253 A1 1/2006 Kosugi
 2006/0033790 A1 2/2006 Shinada et al.
 2006/0119677 A1 6/2006 Shinada et al.
 2006/0203050 A1 9/2006 Shinada et al.
 2006/0250426 A1 11/2006 Wanibe et al.
 2006/0250446 A1 11/2006 Wanibe et al.
 2007/0149044 A1 6/2007 Asauchi
 2008/0158318 A1 7/2008 Asauchi
 2008/0259135 A1 10/2008 Asauchi et al.

FOREIGN PATENT DOCUMENTS

DE 102006060705 A1 6/2007
 EA 1155864 A1 11/2001
 EP 0412459 A2 2/1991
 EP 0593282 A2 4/1994
 EP 0789322 A2 8/1997
 EP 0805028 A1 11/1997
 EP 0812693 A1 12/1997
 EP 0873873 A2 10/1998
 EP 0882595 A2 12/1998
 EP 0997297 A1 5/2000
 EP 1013426 A2 6/2000
 EP 1219437 A2 7/2002
 EP 1279503 A2 1/2003
 EP 1281523 A2 2/2003
 EP 1300245 A1 4/2003
 EP 1314565 A2 5/2003
 EP 1462262 A1 9/2004
 EP 1188567 A2 3/2005
 EP 1514690 A1 3/2005
 EP 1097043 B1 11/2005
 EP 1598198 A2 11/2005
 EP 1792733 A1 6/2007
 EP 1800872 A1 6/2007

EP 2080622 A1 7/2009
 EP 2080622 B1 2/2011
 GB 2369801 A 6/2002
 GB 2424623 A 10/2006
 GB 2446311 A 8/2008
 GB 2447150 A 9/2008
 JP 62-184856 A 8/1987
 JP 02-009645 A 1/1990
 JP 02-279344 A 11/1990
 JP 03-211060 A 9/1991
 JP 05-246032 A 9/1993
 JP 06-320818 A 11/1994
 JP 07-052411 A 2/1995
 JP 07-060954 A 3/1995
 JP 07-309018 11/1995
 JP 08-090871 A 4/1996
 JP 08-221158 A 8/1996
 JP 09-174827 A 7/1997
 JP 10-006535 A 1/1998
 JP 10-086357 A 4/1998
 JP 11-312554 A 11/1999
 JP 11-320857 A 11/1999
 JP 2000-006413 A 1/2000
 JP 2000-198190 A 7/2000
 JP 2001-147146 A 5/2001
 JP 2002-079655 A 3/2002
 JP 2002-154222 A 5/2002
 JP 2002-513340 A 5/2002
 JP 2002-198627 A 7/2002
 JP 2003-054003 A 2/2003
 JP 2003-103796 A 4/2003
 JP 2003-152297 A 5/2003
 JP 2004-050573 A 2/2004
 JP 2004-261970 A 9/2004
 JP 2004-310312 A 11/2004
 JP 2005-161764 A 6/2005
 JP 2005-246664 A 9/2005
 JP 2005-343037 A 12/2005
 JP 2005-372028 12/2005
 JP 2006-100398 A 4/2006
 JP 2007-196664 8/2007
 TW 310363 7/1997
 TW 200520981 7/2005
 TW 200526423 A 8/2005
 WO 98/04414 A1 2/1998
 WO 98/55318 A1 12/1998
 WO 98/55324 A1 12/1998
 WO 02/04215 A1 1/2002
 WO 2005/000591 A1 1/2005
 WO 2006/025578 A1 3/2006
 WO 2006/104258 A1 10/2006
 WO 2006/104258 A1 10/2006

OTHER PUBLICATIONS

The Hard Copy Supplies Journal dated Apr. 1998.
 HP2000C User Guide.
 Dallas Semiconductor, DS1220AB/AD, 16K Nonvolatile SRAM.
 Notice of Opposition for EP2080622 dated Dec. 7, 2011.
 Opposition Form for EP2080622 filed Nov. 28, 2011.
 Grounds of Opposition for EP2080622 dated Nov. 23, 2011 and English translation.
 Decision of Appeal for Invalidation 2011-800028 received Nov. 25, 2011 and English translation.
 HL4a-d, Anspruch 1, 10, 11 and 12—EP2080622BA received at the EPO on Nov. 23, 2011.
 Office Action issued on Oct. 23, 2012 in Taiwan Patent Appln. No. 099126391 and its English Translation.
 U.S. Appl. No. 12/257,827.
 Office Action in U.S. Appl. No. 11/572,880 dated Dec. 7, 2010.
 Notice of Opposition filed against EP1800872B1, Annexes of the Notice of Opposition, and an English translation thereof.
 Accelerated Graphic Port Interface Specification, Jul. 31, 1996, pp. 89-96.
 English Translation of Taiwanese Search Report issued Apr. 22, 2010 in a related Taiwanese application.
 European Patent Office—Extended European Search Report Pursuant to Rule 62 EPC dated Mar. 8, 2010.

US 8,454,116 B2

Page 3

“Written Statement”, in Japanese Patent Document No. 4144637, (original Japanese and English), dated Aug. 26, 2011.

“Dallas Semiconductor DS1220AB/AD 16k Nonvolatile SRAM”, cited in Japanese Patent Document No. 4144637.

“Rebuttal to Corrected Claims”, in Japanese Patent Document No. 4144637, (original Japanese and English) dated Jul. 11, 2011.

“Rebuttal to the Reply Brief”, in Japanese Patent Document No. 4144637, (original Japanese and English) dated Jul. 11, 2011.

“Opinion Brief”, in Japanese Patent Document No. 4144637, (original Japanese and English) dated Jul. 11, 2011.

“Notice of Examination”, in Japanese Patent Document No. 4144637, (original Japanese and English) dated Aug. 22, 2011.

“Notice of Reasons for Rejection (of Amendments)”, in Japanese Patent Document No. 4144637, (original Japanese and English) dated Aug. 26, 2011.

Statement of Defense and Counterclaim dated Dec. 29, 2010 in Dutch Case No. 378291 re EP1800872B and English translation.

Defendant’s Brief dated Dec. 17, 2010 in Japanese Patent Rights Infringement Demand for Injury case 2010 (Wa) No. 7482 (3-20101217) and English translation.

Response to Complaint dated Sep. 17, 2010 in German Action re EP1800872B and English translation.

Response to Complaint dated Sep. 17, 2010 in German Action re Utility Model DE 20 2006 020 730 U1 and English translation.

Allowed claims of U.S. Appl. No. 11/611,641 (published as US-2007/0149044-A1).

Allowed claims of U.S. Appl. No. 12/040,308 (published as US-2008/0158318-A1).

U.S. Appl. No. 12/257,914.

Defendant’s Deed of Appearance and Reply (Italian language version)—Patent infringement litigation based on two counterpart patents EP1800872B1 and IT1374275.

Defendant’s Deed of Appearance and Reply (English language version)—Patent infringement litigation based on two counterpart patents EP1800872B1 and IT1374275.

Defendant’s Second Preparatory Brief dated Feb. 16, 2011; 2010 (Wa) No. 7482 Patents Rights Infringement Demand for Injunction Case for JP4144637B.

International Preliminary Report on Patentability and Written Opinion dated Jul. 1, 2008 in PCT/JP2006/325448.

Spanish Patent Application P200603218 Search Report and Written Opinion dated Sep. 21, 2009.

Malaysian Patent Application PI20091706 Office Action dated Dec. 31, 2010.

European Patent Application EP10184458.7 Search Report dated Dec. 27, 2010.

Summons to Oral Proceeding and Notification in JP4144637B dated Feb. 22, 2011.

Translation of Summons to Oral Proceeding and Notification in JP4144637B dated Feb. 22, 2011.

Opponent’s Comments to the Patent Proprietor’s Rejoinder in the Opposition Proceedings of EP 1 800 872 B1.

Notification of Reason for Rejection of Correction From Proceedings regarding JP Patent No. 4144637, dated Mar. 1, 2011.

Combined Search and Examination Report, U.K. Patent Appln. No. GB 0819699.0, Feb. 27, 2009.

Search and Examination Report issued in counterpart application GB0922617.6 by the Intellectual Property Office of the United Kingdom.

Petition to Tokyo District Court, Civil Affairs Div. 29-C in connection with “2010 (wa) No. 7482 Patent Infringement Injunction” dated Feb. 26, 2010, and English translation thereof.

Defendant’s first preparatory pleadings to Tokyo District Court, Civil Affairs Div. 29-C in connection with 2010 (wa) No. 7482 Patent Infringement Injunction dated Jun. 7, 2010, and English translation thereof.

Australian Search and Examination Report (May 8, 2007) and letter from Singapore Patent Office forwarding same dated Jun. 4, 2007.

U.S. Appl. No. 11/572,880.

New Zealand Examination Report for NZ patent appln. No. 552094 dated Dec. 19, 2006.

United Kingdom Search Report for UK patent appln. No. GB0625839.6 dated Apr. 20, 2007.

Extended European Search Report for European patent appln. No. 06256540.3 dated May 4, 2007.

International Search Report and Written Opinion for international patent appln. No. PCT/JP2006/325448 dated May 8, 2007.

Search Report for PCT/JP2005/016205 dated Nov. 22, 2005.

English translation of Written Opinion of the International Searching Authority issued in PCT/JP2005/016205 dated Mar. 29, 2007.

Allowed claims corresponding to Application No. 2002-167574.

Allowed claims corresponding to Application No. 2002-171700.

Allowed claims corresponding to Application No. 2002-180823.

Allowed claims corresponding to Application No. 2003-58296.

Allowed claims corresponding to Application No. 2006-33790.

Allowed claims corresponding to Application No. 2006-119677.

Search Report from British patent appln. No. GB0804416.6 dated May 30, 2008.

Defendant’s third preparatory pleadings to Tokyo District Court, Civil Affairs Div. 29-C in connection with 2010 (wa) No. 7482 Patent Infringement Injunction dated Sep. 30, 2010.

Defendant’s second preparatory pleadings to Tokyo District Court, Civil Affairs Div. 29-C in connection with 2010 (wa) No. 7482 Patent Infringement Injunction dated Sep. 30, 2010.

Defendant’s Demand for Judgment to Tokyo District Court, Civil Affairs Div. 29-C in connection with 2010 (wa) No. 7482 Patent Infringement Injunction dated Sep. 29, 2010.

Written Submission by Pelikan Hardcopy Production AG in Opposition Proceedings of EP 1 800 872, dated Aug. 31, 2011.

English Translation of Written Submission by Pelikan Hardcopy Production AG in Opposition Proceedings of EP 1 800 872, dated Aug. 31, 2011.

Interlocutory decision in opposition proceedings for EP-B-1 800 872 dated Nov. 29, 2011.

Dallas Semiconductor, DS1220AB/AD, 16K Nonvolatile SRAM, apparently dated Feb. 19, 1998 and listed on an EPO Opposition filing dated Nov. 23, 2011.

Photos of HP No. 10 cartridge listed on an EPO Opposition filing dated Nov. 23, 2011.

HP2000C User Guide listed on an EPO Opposition filing dated Nov. 23, 2011.

Allowed claims corresponding to US Application No. 2006-0033790 filed Oct. 19, 2005.

Allowed claims corresponding to US Application No. 2006-0119677 filed Jan. 30, 2006.

Defendant’s Deed of Appearance and Reply (Italian language version)—Patent infringement litigation based on two counterpart patents EP1800872B1 and IT1374275 dated Feb. 9, 2011.

Defendant’s Deed of Appearance and Reply (English language version)—Patent infringement litigation based on two counterpart patents EP1800872B1 and IT1374275 dated Feb. 9, 2011.

U.S. Appl. No. 11/572,880, filed Jun. 25, 2008.

Opponent’s Comments to the Patent Proprietor’s Rejoinder in the Opposition Proceedings of EP1800872B1 dated Jan. 27, 2011.

Notice of Opposition filed against EP1800872B1, Annexes of the Notice of Opposition, and an English translation thereof dated Dec. 7, 2011.

Search and Examination Report issued in counterpart application GB0922617.6 by the Intellectual Property Office of the United Kingdom dated Mar. 12, 2010.

Allowed claims of U.S. Appl. No. 11/611,641 (published as US-2007/149944-A1) filed Dec. 15, 2006.

Allowed claims of U.S. Appl. No. 12/040,308 (published as US-2008/158318-A1) filed Feb. 29, 2008.

U.S. Appl. No. 12/257,827, filed Oct. 24, 2008.

Allowed claims corresponding to Publication No. US-2002-0167574-A1 published Nov. 14, 2002.

Allowed claims corresponding to Publication No. US-2002-0171700-A1 published Nov. 21, 2002.

Allowed claims corresponding to Application No. US-2002-0180823-A1 published Dec. 5, 2002.

Allowed claims corresponding to Application No. US-2003-0058296-A1 published Mar. 27, 2003.

Response to Appeal dated Oct. 1, 2012 for European Patent No. 1800872 B1.

US 8,454,116 B2

Page 4

English translation of Response to Appeal dated Oct. 1, 2012 for European Patent No. 1800872 B1.

Statement of grounds for appeal for EP 1800872 B1 dated Apr. 10, 2012 and English translation.

Canon Colour Bubble Jet Printer BJC-7000 User Manual dated 1997 and English translation.

Affidavit of Daniel Sulser regarding analysis of “T0714” Epson ink cartridge and “Epson Stylus D78” and photos from Sep. 2006 and English translation.

Article on Epson Stylus D120 dated Dec. 14, 2007 and English translation.

Article on Epson Stylus D78 and D88 plus dated Aug. 21, 2006 and English translation.

Photo of Epson cartridge dated Apr. 10, 2012.

Affidavit of Joachim Kretschmer regarding analysis of “T071x” Epson ink cartridge and “Epson Stylus D78” dated Apr. 10, 2012 and English translation.

U.S. Patent

Jun. 4, 2013

Sheet 1 of 22

US 8,454,116 B2

Fig.1




Fig.2




Fig.3A




Fig.3B




Fig.4




Fig.5




Fig. 6A




Fig. 6B





Fig. 7






Fig.8

Fig.9




Fig.10A




Fig.10B




Fig.10C





Fig.11






Fig. 12A




Fig. 12B
SENSOR VOLTAGE
(NORMAL)




Fig. 12C
SENSOR VOLTAGE
(SHORT IN)

Fig.13




Fig.14A




Fig.14B




Fig.14C




Fig.14D




Fig. 15A




Fig. 15B




Fig. 15C




Fig.16A




Fig.16B




Fig.16C




Fig.16D




Fig.17A




Fig.17B




Fig.17C




Fig.17D




Fig.18A

A-A CROSS SECTION




Fig.18B

B-B CROSS SECTION




Fig.18C

C-C CROSS SECTION




Fig.18D

D-D CROSS SECTION




Fig.19A




Fig.19B




Fig.19C

E-E CROSS SECTION




Fig.19D

F-F CROSS SECTION





Fig.20






Fig. 21

Fig.22




Fig.23





Fig.24



US 8,454,116 B2

1

PRINTING MATERIAL CONTAINER, AND BOARD MOUNTED ON PRINTING MATERIAL CONTAINER

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of copending application Ser. No. 12/257,914, filed Oct. 24, 2008, which is a continuation of application Ser. No. 12/040,308, filed on Feb. 29, 2008, now U.S. Pat. No. 7,484,825, which is a continuation of application Ser. No. 11/611,641, filed on Dec. 15, 2006, now U.S. Pat. No. 7,562,958.

This application relates to and claims priority from Japanese Patent Applications No. 2005-372028, filed on Dec. 26, 2005 and No. 2006-220751, filed on Aug. 11, 2006, the entire disclosures of which are incorporated by reference herein.

BACKGROUND

1. Technical Field

The present invention relates in general to a printing material container containing a printing material and a board mounted on the printing material container, and relates in particular to an arrangement for a plurality of terminals disposed on these components.

2. Description of the Related Art

In recent years, it has become common practice to equip ink cartridges used in ink jet printers or other printing apparatus, with a device, for example, a memory for storing information relating to the ink. Also disposed on such ink cartridges is another device, for example, a high voltage circuit (e.g. a remaining ink level sensor using a piezoelectric element) applied to higher voltage than the driving voltage of the memory. In such cases, there are instances in which the ink cartridge and the printing apparatus are electrically connected through terminals. There is proposed a structure for preventing the information storage medium from shorting and becoming damaged due to a drop of liquid being deposited on the terminals connecting the printing apparatus with the storage medium furnished to the ink cartridge.

However, the technologies mentioned above do not contemplate an ink cartridge having equipped with a plurality of devices, for example, a memory and a high voltage circuit, with terminals for one device and the terminals for another device. With this kind of cartridge, there was a risk that shorting could occur between a terminal for the one device and the terminal for the another device. Such shorting caused the problem of possible damage to the ink cartridge or to the printing apparatus in which the ink cartridge is attached. This problem is not limited to ink cartridges, but is a problem common to receptacles containing other printing materials, for example, toner.

SUMMARY

An advantage of some aspects of the present invention is to provide a printing material container having a plurality of devices, wherein damage to the printing material container and the printing apparatus caused by shorting between terminals can be prevented or reduced.

A first aspect of the invention provides a printing material container detachably attachable to a printing apparatus having a plurality of apparatus-side terminals. The printing material container pertaining to the first aspect of the invention comprises a first device, a second device and a terminal group that includes a plurality of first terminals, at least one second

2

terminal and at least one third terminal. The plurality of first terminals are connected to the first device and respectively include a first contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one second terminal is connected to the second device and includes a second contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal and includes a third contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one second contact portion, the plurality of the first contact portions, and the at least one third contact portion are arranged so as to form one or multiple rows. The at least one second contact portion is arranged at an end of one row among the one or multiple rows.

According to the printing material container pertaining to the first aspect of the invention, the second contact portions of the second terminals connected to the second device are arranged at the ends, whereby other contact portions adjacent to the second contact portions are fewer in number, and consequently the second terminals have less likelihood of shorting to terminals include other contact portions. Accordingly, damage to the printing material container or printing apparatus caused by such shorting can be prevented or reduced.

A second aspect of the invention provides printing material container detachably mountable to a printing apparatus having a plurality of apparatus-side terminals. The printing material container pertaining to the second aspect of the invention comprises a first device, a second device, a group of terminals for connection to the apparatus-side terminals and comprising a plurality of first terminals, at least one second terminal, and at least one third terminal. The plurality of first terminals are connected to the first device. The at least one second terminal is connected to the second device. At least a portion of the at least one third terminal is arranged relative to at least a portion of the at least one second terminal, without a said first terminal therebetween in at least one direction, for the detection of shorting between the at least one second terminal and the at least one third terminal.

According to the printing material container pertaining to the second aspect of the invention, at least a portion of the at least one third terminal is arranged relative to at least a portion of the at least one second terminal, without a said first terminal therebetween in at least one direction. As a result, shorting between the portion of the at least one third terminal and the portion of the at least one second terminal have a greater tendency to occur than shorting between the first terminal and the second terminal. Accordingly, in the event that the shorting between the first terminal and the second terminal occurs by a drop of ink or foreign matter, it is highly likely that the shorting between the portion of the at least one third terminal and the portion of the at least one second terminal also occurs, and is detected as anomaly. As a result, damage to the printing material container or printing apparatus caused by a shorting between the first terminal and the second terminal can be prevented or reduced.

A third aspect of the invention provides a printing material container detachably mountable to a printing apparatus having a plurality of apparatus-side terminals. The printing material container pertaining to the third aspect of the invention comprises a first device, a second device, a group of terminals for connection to the apparatus-side terminals and comprising a plurality of first terminals, at least one second terminal, and at least one third terminal. The plurality of first terminals are connected to the first device. The at least one second terminal is connected to the second device. The at least one

US 8,454,116 B2

3

third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal. At least a portion of the at least one third terminal is located adjacently to at least a portion of the at least one second terminal in at least one direction.

According to the printing material container pertaining to the third aspect of the invention, at least a portion of the at least one third terminal is located adjacently to at least a portion of the at least one second terminal. As a result, shorting between the portion of the at least one third terminal and the portion of the at least one second terminal have a greater tendency to occur than shorting between the first terminal and the second terminal. Accordingly, in the event that the shorting between the first terminal and the second terminal occurs by a drop of ink or foreign matter, it is highly likely that the shorting between the portion of the at least one third terminal and the portion of the at least one second terminal also occurs, and is detected as anomaly. As a result, damage to the printing material container or printing apparatus caused by a shorting between the first terminal and the second terminal can be prevented or reduced.

A fourth aspect of the invention provides printing material container detachably mountable to a printing apparatus having a apparatus-side terminal group. The apparatus-side terminal group includes a plurality of first apparatus-side terminals, a plurality of second apparatus-side terminals, and a plurality of third apparatus-side terminals. Terminals within the apparatus-side terminal group are arranged so as to form a first row and second row. The plurality of second apparatus-side terminals are respectively arranged at each end of the first row and the third apparatus-side terminals are respectively arranged at each end of the second row. Each of the second apparatus-side terminals is adjacent to any of the third apparatus-side terminals. The printing material container pertaining to the fourth aspect of the invention comprises a first device, a second device, a group of terminals comprising a plurality of first terminals, at least one second terminal, and at least one third terminal. The plurality of first terminals are connected to the first device and are respectively contactable to a corresponding terminal among the first apparatus-side terminals. The at least one second terminal is connected to the second device and is respectively contactable to a corresponding terminal among the second apparatus-side terminals. The at least one third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal and is respectively contactable to a corresponding terminal among the third apparatus-side terminals.

The printing material container pertaining to the fourth aspect of the invention can afford working effects analogous to those of the printing material container pertaining to the first aspect. The printing material container pertaining to the fourth aspect of the invention may be reduced to practice in various forms, in the same manner as the printing material container which pertaining to the first aspect.

A fifth aspect of the invention provides a printing material container detachably attachable to a printing apparatus having a plurality of apparatus-side terminals. The printing material container pertaining to the fifth aspect of the invention comprises a first device, a second device, and a terminal group that includes a plurality of first terminals, at least one second terminal and at least one third terminal. The plurality of first terminals are connected to the first device. The at least one second terminal is connected to the second device. The at least one third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal. Each of the terminals has an circumferential

4

edge, a portion of the circumferential edge of the third terminal facing a portion of the circumferential edge of the second terminal and a portion of the circumferential edge of the one first terminal facing another portion of the circumferential edge of the second terminal. The length of the portion of circumferential edge of the third terminal is longer than that of the portion of the circumferential edge of the one first terminal.

According to the printing material container pertaining to the fifth aspect of the invention, the length of the portion of circumferential edge of the third terminal is longer than that of the portion of the circumferential edge of the one first terminal. As a result, shorting between the third terminal and the second terminal have a greater tendency to occur than shorting between the first terminal and the second terminal. Accordingly, in the event that the shorting between the first terminal and the second terminal occurs by a drop of ink or foreign matter, it is highly likely that the shorting between the portion of the at least one third terminal and the portion of the at least one second terminal also occurs, and is detected as anomaly. As a result, damage to the printing material container or printing apparatus caused by a shorting between the first terminal and the second terminal can be prevented or reduced.

A sixth aspect of the invention provides a board mountable on a printing material container detachably attachable to a printing apparatus that has a plurality of apparatus-side terminals. The printing material container has second device. The board pertaining to the sixth aspect of the invention comprises a first device and a terminal group that includes a plurality of first terminals, at least one second terminal and at least one third terminal. The plurality of first terminals are connected to the first device and respectively include a first contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one second terminal is connectable to the second device and includes a second contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal and includes a third contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one second contact portion, the plurality of the first contact portions, and the at least one third contact portion are arranged so as to form one or multiple rows. The at least one second contact portion is arranged at an end of one row among the one or multiple rows.

A seventh aspect of the invention provides a board mountable on a printing material container detachably attachable to a printing apparatus that has a plurality of apparatus-side terminals. The printing material container has second device. The board pertaining to the seventh aspect of the invention comprises a first device and a group of terminals for connection to the apparatus-side terminals and comprising a plurality of first terminals, at least one second terminal, and at least one third terminal. The plurality of first terminals are connected to the first device. The at least one second terminal is connected to the second device. At least a portion of the at least one third terminal is arranged relative to at least a portion of the at least one second terminal, without a said first terminal therebetween in at least one direction, for the detection of shorting between the at least one second terminal and the at least one third terminal.

An eighth aspect of the invention provides a board mountable on a printing material container detachably attachable to a printing apparatus that has a plurality of apparatus-side terminals. The printing material container has second device.

5

The board pertaining to the eighth aspect of the invention comprises a first device and a group of terminals for connection to the apparatus-side terminals and comprising a plurality of first terminals, at least one second terminal, and at least one third terminal. The plurality of first terminals are connected to the first device. The at least one second terminal is connected to the second device. The at least one third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal. At least a portion of the at least one third terminal is located adjacently to at least a portion of the at least one second terminal in at least one direction.

A ninth aspect of the invention provides a board mountable on a printing material container detachably attachable to a printing apparatus having a apparatus-side terminal group that includes a plurality of first apparatus-side terminals, a plurality of second apparatus-side terminals, and a plurality of third apparatus-side terminals. Terminals within the apparatus-side terminal group are arranged so as to form a first row and second row. The plurality of second apparatus-side terminals are respectively arranged at each end of the first row and the third apparatus-side terminals are respectively arranged at each end of the second row. Each of the second apparatus-side terminals is adjacent to any of the third apparatus-side terminals. The printing material container has second device. The board pertaining to the ninth aspect of the invention comprises a first device and a group of terminals comprising a plurality of first terminals, at least one second terminal, and at least one third terminal. The plurality of first terminals are connected to the first device and are respectively contactable to a corresponding terminal among the first apparatus-side terminals. The at least one second terminal is connected to the second device and is respectively contactable to a corresponding terminal among the second apparatus-side terminals. The at least one third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal and is respectively contactable to a corresponding terminal among the third apparatus-side terminals.

A tenth aspect of the invention provides a board mountable on a printing material container detachably attachable to a printing apparatus that has a plurality of apparatus-side terminals. The printing material container has second device. The board pertaining to the tenth aspect of the invention comprises a first device and a terminal group that includes a plurality of first terminals, at least one second terminal and at least one third terminal. The plurality of first terminals are connected to the first device. The at least one second terminal is connected to the second device. The at least one third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal. Each of the terminals has a circumferential edge, a portion of the circumferential edge of the third terminal facing a portion of the circumferential edge of the second terminal and a portion of the circumferential edge of the one first terminal facing another portion of the circumferential edge of the second terminal. The length of the portion of circumferential edge of the third terminal is longer than that of the portion of the circumferential edge of the one first terminal.

An eleventh aspect of the invention provides a board mountable on a printing material container detachably attachable to a printing apparatus that has a plurality of apparatus-side terminals. The printing material container has a second device. The board pertaining to the eleventh aspect of the invention comprises a first device and a terminal group that includes at least a plurality of first terminals, at least one cut-out portions into which a respective second terminal

6

mounted on the printing material container can be inserted and at least one third terminal. The plurality of first terminals are connectable to the first device and respectively include a first contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one second terminal is connectable to the second device and includes a second contact portion for contacting a corresponding terminal among the plurality of apparatus-side-terminals. The at least one third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal and includes a third contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. When mounted on the printing material container, the at least one third contact portion is located adjacently to the at least one second contact portion. When mounted on the printing material container, the at least one second contact portion, the plurality of the first contact portions, and the at least one third contact portion are arranged so as to form one or multiple rows. When mounted on the printing material container, the at least one second contact portion is arranged at an end of one row among the one or multiple rows.

A twelfth aspect of the invention provides a board connectable to a printing apparatus that has a plurality of apparatus-side terminals. The board pertaining to the twelfth aspect of the invention comprises a terminal group that includes a plurality of first terminals, at least one second terminal and at least one third terminal. The plurality of first terminals are connected to a first device and respectively include a first contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one second terminal is connectable to a second device and includes a second contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one third terminal is for the detection of shorting between the at least one second terminal and the at least one third terminal and includes a third contact portion for contacting a corresponding terminal among the plurality of apparatus-side terminals. The at least one second contact portion, the plurality of the first contact portions, and the at least one third contact portion are arranged so as to form one or multiple rows. The at least one second contact portion is arranged at an end of one row among the one or multiple rows.

The boards pertaining to the sixth to the twelfth aspects of the invention can afford working effects analogous to those of the printing material container pertaining to the first to the fifth aspects respectively. The boards pertaining to the sixth to eleventh aspects may be reduced to practice in various forms, in the same manner as the printing material container pertaining to the first to the fifth aspects respectively.

The above and other objects, characterizing features, aspects and advantages of the present invention will be clear from the description of preferred embodiments presented below along with the attached figures.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a perspective view of the construction of the printing apparatus pertaining to an embodiment of the invention;

FIG. 2 shows a perspective view of the construction of the ink cartridge pertaining to the embodiment;

FIGS. 3A-B show diagrams of the construction of the board pertaining to the embodiment;

FIG. 4 shows an illustration showing attachment of the ink cartridge in the holder;

US 8,454,116 B2

7

FIG. 5 shows an illustration showing the ink cartridge attached to the holder;

FIGS. 6A-B show schematics of the construction of the contact mechanism;

FIG. 7 shows a brief diagram of the electrical arrangement of the ink cartridge and the printing apparatus;

FIG. 8 shows a brief diagram of the electrical arrangement, focusing on the cartridge detection/short detection circuit;

FIG. 9 shows a flowchart depicting the processing routine of the cartridge determination process;

FIGS. 10A-C show illustrations depicting three types of terminal lines on the board;

FIG. 11 shows a flowchart depicting the processing routine of the remaining ink level detection process;

FIGS. 12A-C show timing charts depicting temporal change in the shorting-detection enable signal and sensor voltage during execution of the remaining ink level detection process;

FIG. 13 shows an illustration of a scenario of shorting;

FIGS. 14A-D show first diagrams depicting boards pertaining to variations;

FIGS. 15A-C show second diagrams depicting boards pertaining to variations;

FIGS. 16A-D show third diagrams depicting boards pertaining to variations;

FIGS. 17A-D show diagrams depicting the construction around boards of ink cartridges pertaining to variations;

FIGS. 18A-D show cross sections A-A to D-D in FIG. 17;

FIGS. 19A-D show fourth diagrams depicting boards pertaining to variations;

FIG. 20 shows a perspective view of the construction of the ink cartridge pertaining to a variation;

FIG. 21 shows a picture of the ink cartridge pertaining to a variation being attached to the printer;

FIG. 22 shows a first diagram of the construction of the ink cartridge pertaining to a variation;

FIG. 23 shows a second diagram of the construction of the ink cartridge pertaining to a variation;

FIG. 24 shows a third diagram of the construction of the ink cartridge pertaining to a variation.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be described below with reference to the drawings.

A. Embodiment

Arrangement of Printing Apparatus and Ink Cartridge:

FIG. 1 shows a perspective view of the construction of the printing apparatus pertaining to an embodiment of the invention. The printing apparatus 1000 has a sub-scan feed mechanism, a main scan feed mechanism, and a head drive mechanism. The sub-scan feed mechanism carries the printing paper P in the sub-scanning direction using a paper feed roller 10 powered by a paper feed motor, not shown. The main scan feed mechanism uses the power of a carriage motor 2 to reciprocate in the main scanning direction a carriage 3 connected to a drive belt. The head drive mechanism drives a print head 5 mounted on the carriage 3, to eject ink and form dots. The printing apparatus 1000 additionally comprises a main control circuit 40 for controlling the various mechanisms mentioned above. The main control circuit 40 is connected to the carriage 3 via a flexible cable 37.

The carriage 3 comprises a holder 4, the print head 5 mentioned above, and a carriage circuit, described later. The holder 4 is designed for attachment of a number of ink cartridges, described later, and is situated on the upper face of the

8

print head 5. In the example depicted in FIG. 1, the holder 4 is designed for attachment of four ink cartridges, e.g. individual attachment of four types of ink cartridge containing black, yellow, magenta, and cyan ink. Four openable and closable covers 11 are attached to the holder 4 for each attached ink cartridge. Also disposed on the upper face of the print head 5 are ink supply needles 6 for supplying ink from the ink cartridges to the print head 5.

The construction of the ink cartridge pertaining to the embodiment will now be described with reference of FIGS. 2-5. FIG. 2 shows a perspective view of the construction of the ink cartridge pertaining to the embodiment. FIGS. 3A-B show diagrams of the construction of the board pertaining to the embodiment. FIG. 4 shows an illustration showing attachment of the ink cartridge in the holder. FIG. 5 shows an illustration showing the ink cartridge attached to the holder. The ink cartridge 100 attached to the holder 4 comprises a housing 101 containing ink, a lid 102 providing closure to the opening of the housing 101, a board 200, and a sensor 104. On the bottom face of the housing 101 there is formed an ink supply orifice 110 into which the aforementioned ink supply needle 6 inserts when ink cartridge 100 is attached to the holder 4. At the upper edge of the front face FR of the housing 101 there is formed a flared section 103. On the lower side of the center of the front face FR of the housing 101 there is formed a recess 105 bounded by upper and lower ribs 107, 106. The aforementioned board 200 fits into this recess 105. The sensor 104 is located in the region posterior to the board 200. The sensor 104 is used to detect remaining ink level, as will be described later.

FIG. 3A depicts the arrangement on the surface of the board 200. This surface is the face that is exposed to the outside when the board 200 is mounted on the ink cartridge 100. FIG. 3B depicts the board 200 viewed from the side. A boss slot 201 is formed at the upper edge of the board 200, and a boss hole 202 is formed at the lower edge of the board 200. As shown in FIG. 1, with the board 200 attached to the recess 105 of the housing 101, bosses 108 and 109 formed on the lower face of the recess 105 mate with the boss slot 201 and the boss hole 202 respectively. The distal ends of the bosses 108 and 109 are crushed to effect caulking. The board 200 is secured within the recess 105 thereby.

The following description of attachment of the ink cartridge 100 makes reference to FIG. 4 and FIG. 5. As depicted in FIG. 4, the cover 11 is designed to be rotatable about a rotating shaft 9. With the cover 11 rotated upward to the open position, when the ink cartridge 100 is being attached to the holder, the flared section 103 of the ink cartridge is received by a projection 14 of the cover 11. When the cover 11 is closed from this position, the projection 14 rotates downward, and the ink cartridge 100 descends downward (in the Z direction in FIG. 4). When the cover 11 is completely closed, a hook 18 of the cover 11 interlocks with a hook 16 of the holder 4. With the cover 11 completely closed, the ink cartridge 100 is secured pressed against the holder 4 by an elastic member 20. Also, with the cover 11 completely closed, the ink supply needle 6 inserts into the ink supply orifice 110 of the ink cartridge 100, and the ink contained in the ink cartridge 100 is supplied to the printing apparatus 1000 via the ink supply needle 6. As will be apparent from the preceding description, the ink cartridge 100 is attached to the holder 4 by means of inserting it so as to move in the forward direction of the Z axis in FIG. 4 and FIG. 5. The forward direction of the Z axis in FIG. 4 and FIG. 5 shall also be referred to as insertion direction of the ink cartridge 100.

Returning to FIG. 3, the board 200 shall be described further. The arrow R in FIG. 3(a) indicates the insertion

US 8,454,116 B2

9

direction of the ink cartridge **100** discussed above. As depicted in FIG. 3, the board **200** comprises a memory **203** disposed on its back face, and a terminal group composed of nine terminals **210-290** disposed on its front face. The memory **203** stores information relating to the ink contained in the ink cartridge **100**. The terminals **210-290** are generally rectangular in shape, and are arranged in two rows generally orthogonal to the insertion direction R. Of the two rows, the row on the insertion direction R side, i.e. the row situated on the lower side in FIG. 3(a), shall be termed the lower row, and the row on the opposite side from the insertion direction R, i.e. the row situated on the upper side in FIG. 3(a), shall be termed the upper row. The terminals arranged so as to form the upper row consist, in order from left in FIG. 3(a), of a first short detection terminal **210**, a ground terminal **220**, a power supply terminal **230**, and a second short detection terminal **240**. The terminals arranged so as to form the lower row consist, in order from left in FIG. 3(a), of a first sensor drive terminal **250**, a reset terminal **260**, a clock terminal **270**, a data terminal **280**, and a second sensor drive terminal **290**. As depicted in FIG. 3, each of the terminals **210-290** contains in its center portion a contact portion CP for contacting a corresponding terminal among the plurality of apparatus-side terminals, described later.

The terminals **210-240** forming the upper row and the terminals **250-290** forming the lower row are arranged differently from one another, constituting a so-called staggered arrangement, so that the terminal centers do not line up with one another in the insertion direction R. As a result, the contact portions CP of the terminals **210-240** forming the upper row and the contact portions CP of the terminals **250-290** forming the lower row are similarly arranged differently from one another, constituting a so-called staggered arrangement.

As will be appreciated from FIG. 3A, the first sensor drive terminal **250** is situated adjacently to two other terminals (the reset terminal **260** and the first short detection terminal **210**), and of these, the first short detection terminal **210** for detecting shorting is positioned closest to the first sensor drive terminal **250**. Similarly, the second sensor drive terminal **290** is situated adjacently to two other terminals (the second short detection terminal **240** and the data terminal **280**), and of these, the second short detection terminal **240** for detecting shorting is positioned closest to the second sensor drive terminal **290**.

With regard to relationships among the contact portions CP, the contact portion CP of the first sensor drive terminal **250** is situated adjacently to the contact portions CP of two other terminals (the reset terminal **260** and the first short detection terminal **210**). Similarly, the contact portion CP of the second sensor drive terminal **290** is situated adjacently to the contact portions CP of two other terminals (the second short detection terminal **240** and the data terminal **280**).

As will be appreciated from FIG. 3A, the first sensor drive terminal **250** and the second sensor drive terminal **290** are situated at the ends of the lower row, i.e. at the outermost positions in the lower row. The lower row is composed of a greater number of terminals than the upper row, and the length of the lower row in the direction orthogonal to the insertion direction R is greater than the length of the upper row, and consequently of all the terminals **210-290** contained in the upper and lower rows, the first sensor drive terminal **250** and the second sensor drive terminal **290** are situated at the outermost positions viewed in the direction orthogonal to the insertion direction R.

With regard to relationships among the contact portions CP, the contact portion CP of the first sensor drive terminal

10

250 and the contact portion CP of the second sensor drive terminal **290** are respectively situated at the ends of the lower row formed by the contact portions CP of the terminals, i.e., at the outermost positions in the lower row. Among the contact portions of all the terminals **210-290** contained in the upper and lower rows, the contact portion CP of the first sensor drive terminal **250** and the contact portion CP of the second sensor drive terminal **290** are situated at the outermost positions viewed in the direction orthogonal to the insertion direction R.

As will be appreciated from FIG. 3A, the first short detection terminal **210** and the second short detection terminal **240** are respectively situated at the ends of the upper row, i.e., at the outermost positions in the upper row. As a result, the contact portion CP of the first short detection terminal **210** and the contact portion CP of the second short detection terminal **240** are similarly located at the ends of the upper row formed by the contact portions CP of the terminals, i.e. at the outermost positions in the upper row. Consequently, as will be discussed later, the terminals **220**, **230**, **260**, **270** and **280** connected to the memory **203** are situated between the first short detection terminal **210** and the first sensor drive terminal **250**, and the second short detection terminal **240** and the second sensor drive terminal **290**, located to either side.

In the embodiment, the board **200** has width of approximately 12.8 mm in the insertion direction R, width of the approximately 10.1 mm in the direction orthogonal to the insertion direction R, and thickness of approximately 0.71 mm. The terminals **210-290** each have width of approximately 1.8 mm in the insertion direction R and width of approximately 1.05 mm in the direction orthogonal to the insertion direction R. The dimension values given here are merely exemplary, with differences on the order of ± 0.5 mm being acceptable, for example. The spacing between adjacent terminals in a given row (the lower row or the upper row), for example the interval K between the first short detection terminal **210** and the ground terminal **220**, is 1 mm for example. With regard to spacing among terminals, differences on the order of ± 0.5 mm are acceptable, for example. The interval J between the upper row and the lower row is about 0.2 mm. With regard to spacing among rows, differences on the order of ± 0.3 mm are acceptable, for example.

As depicted in FIG. 5, with the ink cartridge **100** attached completely within the holder **4**, the terminals **210-290** of the board **200** are electrically connected to a carriage circuit **500** via a contact mechanism **400** disposed on the holder **4**. The contact mechanism **400** shall be described briefly making reference to FIGS. 6A-B.

FIGS. 6A-B show schematics of the construction of the contact mechanism **400**. The contact mechanism **400** has multiple slits **401**, **402** of two types that differ in depth, formed in alternating fashion at substantially constant pitch in correspondence with the terminals **210-290** on the board **200**. Within each slit **401**, **402** there fits a contact forming member **403**, **404** endowed with electrical conductivity and resistance. Of the two ends of each contact forming member **403** and **404**, the end exposed to the inside of the holder is placed in resilient contact with a corresponding terminal among the terminals **210-290** on the board **200**. In FIG. 6A, portions **410-490** which are the portions of the contact forming members **403** and **404** that contact the terminals **210-290** are shown. Specifically, the portions **410-490** that contact the terminals **210-290** function as apparatus-side terminals for electrically connecting the printing apparatus **1000** with the terminals **210-290**. The portions **410-490** that contact the terminals **210-290** shall hereinafter be termed apparatus-side terminals **410-490**. With the ink cartridge **100** attached to the holder **4**, the appa-

US 8,454,116 B2

11

ratus-side terminals 410-490 respectively contact the contact portions CP of the terminals 210-290 described above (FIG. 3A).

On the other hand, of the two ends of each contact forming member 403 and 404, the end lying exposed on the exterior of the holder 4 is placed in resilient contact with a corresponding terminal among the terminals 510-590 furnished to the carriage circuit 500.

The electrical arrangements of the ink cartridge 100 and the printing apparatus will now be described, focusing on the part relating to the ink cartridge 100, with reference to FIG. 7 and FIG. 8. FIG. 7 shows a brief diagram of the electrical arrangement of the ink cartridge and the printing apparatus. FIG. 8 shows a brief diagram of the electrical arrangement, focusing on the cartridge detection/short detection circuit.

First, the electrical arrangement of the ink cartridge 100 shall be described. Of the terminals of the board 200 described with reference to FIG. 3, the ground terminal 220, the power supply terminal 230, the reset terminal 260, the clock terminal 270 and the data terminal 280 are electrically connected to the memory 203. The memory 203 is, for example, EEPROM comprising serially accessed memory cells, and performing data read/write operations in sync with a clock signal. The ground terminal 220 is grounded via a terminal 520 on the printing apparatus 1000 side. The reset terminal 260 is electrically connected to a terminal 560 of the carriage circuit 500, and is used to supply a reset signal RST to the memory 203 from the carriage circuit 500. The clock terminal 270 is electrically connected to a terminal 570 of the carriage circuit 500, and is used to supply the clock signal CLK to the memory 203 from the carriage circuit 500. The data terminal 280 is electrically connected to a terminal 580 of the carriage circuit 500, and is used for exchange of data signals SDA between the carriage circuit 500 and the memory 203.

Of the terminals of the board 200 described with reference to FIG. 3, either the first short detection terminal 210, the second short detection terminal 240, or both are electrically connected with the ground terminal 220. In the example depicted in FIG. 7, it will be apparent that the first short detection terminal 220 is electrically connected to the ground terminal 220. The first short detection terminal 210 and the second short detection terminal 240 are electrically connected respectively to the terminals 510, 540 of the carriage circuit 500, and used for cartridge detection and short detection, described later.

In the embodiment, a piezoelectric element is used as the sensor 104. The remaining ink level can be detected by applying driving voltage to the piezoelectric element to induce the piezoelectric element to vibrate through the inverse piezoelectric effect, and measuring the vibration frequency of the voltage produced by the piezoelectric effect of the residual vibration. Specifically, this vibration frequency represents the characteristic frequency of the surrounding structures (e.g. the housing 101 and ink) that vibrate together with the piezoelectric element. The characteristic frequency changes depending on the amount of ink remaining within the ink cartridge, so the remaining ink level can be detected by measuring this vibration frequency. Of the terminals of the board 200 described with reference to FIG. 3, the second sensor drive terminal 290 is electrically connected to one electrode of the piezoelectric element used as the sensor 104, and the first sensor drive terminal 250 is electrically connected to the other electrode. These terminals 250, 290 are used for exchange of sensor driving voltage and output signals from the sensor 104, between the carriage circuit 500 and the sensor 104.

12

The carriage circuit 500 comprises a memory control circuit 501, a cartridge detection/short detection circuit 502, and a sensor driving circuit 503. The memory control circuit 501 is a circuit connected to the terminals 530, 560, 570, 580 of the carriage circuit 500 mentioned above, and used to control the memory 203 of the ink cartridge 100 to perform data read/write operations. The memory control circuit 501 and the memory 203 are low-voltage circuits driven at relatively low voltage (in the embodiment, a maximum of about 3.3 V). The memory control circuit 501 can employ a known design, and as such need not be described in detail here.

The sensor driving circuit 503 is a circuit connected to the terminals 590 and 550 of the carriage circuit 500, and used to control the driving voltage output from these terminals 590 and 550 to drive the sensor 104, causing the sensor 104 to detect the remaining ink level. As will be described later, the driving voltage has a generally trapezoidal shape, and contains relatively high voltage (in the embodiment, about 36 V). Specifically, the sensor driving circuit 503 and the sensor 104 are high-voltage circuits using relatively high voltage via the terminals 590 and 550. The sensor driving circuit 503 is composed of a logic circuit for example, but need not be described in detail herein.

The cartridge detection/short detection circuit 502, like the memory control circuit 501, is a low-voltage circuit driven using relatively low voltage (in the embodiment, a maximum of about 3.3 V). As depicted in FIG. 8, the cartridge detection/short detection circuit 502 comprises a first detection circuit 5021 and a second detection circuit 5022. The first detection circuit 5021 is connected to the terminal 510 of the carriage circuit 500. The first detection circuit 5021 has a cartridge detection function for detecting whether there is contact between the terminal 510 and the first short detection terminal 210 of the board 200, and a short detection function for detecting shorting of the terminal 510 to the terminals 550 and 590 which output high voltage.

To describe in more specific terms, the first detection circuit 5021 has a reference voltage V_{ref1} applied to one end of two series-connected resistors R2, R3, with the other end being grounded, thereby maintaining the potential at point P1 and P2 in FIG. 4 at V_{ref1} and V_{ref2} , respectively. Herein V_{ref1} shall be termed the short detection voltage, and V_{ref2} shall be termed the cartridge detection voltage. In the embodiment, the short detection voltage V_{ref1} is set to 6.5 V, and the cartridge detection voltage V_{ref2} is set to 2.5 V. These values are established by means of the circuits, and are not limited to the values given herein.

As depicted in FIG. 8, the short detection voltage V_{ref1} (6.5 V) is input to the negative input pin of a first Op-Amp OP1, while the cartridge detection voltage V_{ref2} (2.5 V) is input to the negative input pin of a second Op-Amp OP2. The potential of the terminal 510 is input to the positive input pins of the first Op-Amp OP1 and the second Op-Amp OP2. These two Op-Amps function as a comparator, outputting a High signal when the potential input to the negative input pin is higher than the potential input to the positive input pin, and conversely outputting a Low signal when the potential input to the negative input pin is lower than the potential input to the positive input pin.

As depicted in FIG. 8, the terminal 510 is connected to a 3.3 V power supply VDD 3.3 via a transistor TR1. By means of this arrangement, if terminal 510 is free e.g. there is no contact with terminal 510, the potential of the terminal 510 will be set at about 3 V. As noted, when the ink cartridge 100 is attached, the terminal 510 comes into contact with the first short detection terminal 210 of the board 200 described previously. Here, as depicted in FIG. 7, with the first short detection terminal

US 8,454,116 B2

13

210 and the ground terminal 220 electrically connected (shorted) in the board 200, when the terminal 510 comes into contact with the first short detection terminal 210 (herein referred to as being in contact), the terminal 510 is electrically continuous with the grounded terminal 520, and the potential of the terminal 510 drops to 0 V.

Consequently, with the terminal 510 free, a High signal from the second Op-Amp OP2 is output as the cartridge detection signal CS1. With the terminal 510 in contact, a Low signal from the second Op-Amp OP2 is output as the cartridge detection signal CS1.

On the other hand, if the terminal 510 is shorted to the adjacent terminal 550, there are instances in which the sensor driving voltage (45 V max) will be applied to the terminal 510. As shown in FIG. 8, when voltage greater than the short detection voltage V_{ref1} (6.5 V) is applied to the terminal 510 due to shorting, a High signal from the Op-Amp OP1 will be output to an AND circuit AA.

As shown in FIG. 8, a short detection enable signal EN is input from the main control circuit 40 to the other input pin of the AND circuit AA. As a result, only during the time interval that a High signal is input as the short detection enable signal EN, the first detection circuit 5021 outputs the High signal from the Op-Amp OP1 as a short detection signal AB1. That is, execution of the short detection function of the first detection circuit 5021 is controlled by means of the short detection enable signal EN of the main control circuit 40. The short detection signal AB1 from the AND circuit AA is output to the main control circuit 40, as well as being output to the base pin of the transistor TR1 via resistance R1. As a result, by means of the transistor TR1 it is possible to prevent high voltage from being applied to the power supply VDD 3.3 via the terminal 510 when a short is detected (when the short detection signal AB1 is HI).

The second detection circuit 5022 has a cartridge detection function for detecting whether there is contact between the terminal 540 and the second short detection terminal 240 of the board 200, and a short detection function for detecting shorting of the terminal 540 to the terminals 550 and 590 which output high voltage. Since the second detection circuit 5022 has the same arrangement as the first detection circuit 5021, a detailed illustration and description need not be provided here. Hereinafter, the cartridge detection signal output by the second detection circuit 5022 shall be denoted as CS2, and the short detection signal as AB2.

An arrangement of the carriage circuit 500 corresponding to a single ink cartridge 100 has been described above. In the embodiment, since four ink cartridges 100 are attached, four of the cartridge detection/short detection circuits 502 described above will be provided, at each of the attachment locations for the four ink cartridges 100. While only a single sensor driving circuit 503 is provided, and a single sensor driving circuit 503 is connectable to each of the sensors 104 of the ink cartridges 100 attached at the four attachment locations by means of a switch(not shown). The memory control circuit 501 is a single circuit responsible for processes relating to the four ink cartridges.

The main control circuit 40 is a computer of known design comprising a central processing unit (CPU), a read-only memory (ROM), and a random access memory (RAM). As noted, the main control circuit 40 controls the entire printer; in FIG. 8, however, only those elements necessary for description of the embodiment are selectively illustrated, and the following description refers to the illustrated arrangement. The main control circuit 40 comprises a cartridge determining module M50 and a remaining ink level determining module M60. On the basis of the received cartridge detection

14

signals CS1, CS2, the cartridge determining module M50 executes a cartridge determination process, described later. The remaining ink level determining module M60 controls the sensor driving circuit 503, and executes a remaining ink level detection process, described later.

Cartridge Determination Process:

The cartridge determination process executed by the cartridge determining module M50 of the main control circuit 40 will be described with reference to FIG. 9 and FIG. 10. FIG. 9 shows a flowchart depicting the processing routine of the cartridge determination process. FIGS. 10A-C show illustrations depicting three types of terminal lines on the board 200.

Before turning to the cartridge determination process, the board 200 will be described further with reference to FIG. 10. The board 200 mentioned previously comes in three types, depending on the wiring pattern of the first short detection terminal 210, the second short detection terminal 240, and the ground terminal 220. These three types are designated respectively as Type A, Type B, and Type C. As depicted in FIG. 10A, the Type A board 200 is arranged with the first short detection terminal 210 and the ground terminal 220 electrically connected by a conducting line 207, while the second short detection terminal 240 and the ground terminal 220 are not electrically connected. As depicted in FIG. 10B, the Type B board 200 is arranged with both the first short detection terminal 210 and the second short detection terminal 240 electrically connected with the ground terminal 220 by a conducting line 207. As depicted in FIG. 10C, the Type C board 200 is arranged with the second short detection terminal 240 and the ground terminal 220 electrically connected by a conducting line 207, while the first short detection terminal 210 and the ground terminal 220 are not electrically connected. A board 200 of predetermined type, selected with reference to ink type or ink quantity for example, is disposed on the ink cartridge 100. Specifically, depending on the quantity of ink contained in the ink cartridge 100, a Type A board 200 could be disposed on an L size cartridge containing a large quantity of ink; a Type B board 200 could be disposed on an M size cartridge containing a standard quantity of ink; and a Type C board 200 could be disposed on an S size cartridge containing a small quantity of ink.

The cartridge determining module M50 of the main control circuit 40 constantly receives from the cartridge detection/short detection circuit 502 the cartridge detection signals CS1, CS2 for each of the four attachment locations of the holder 4, and using these signals executes the cartridge determination process for each of the attachment locations.

When the cartridge determining module M50 initiates the cartridge determination process for a selected attachment location, the cartridge determining module M50 first ascertains whether the cartridge detection signal CS1 from the cartridge detection/short detection circuit 502 in the selected attachment location is a Low signal (Step S102). Next, the cartridge determining module M50 ascertains whether the cartridge detection signal CS2 in the selected attachment location is a Low signal (Step S104 or S106). If as a result the cartridge detection signals CS1 and CS2 are both Low signals (Step S102: YES and Step S104: YES), the cartridge determining module M50 decides that the ink cartridge 100 attached to the selected attachment location is furnished with the Type B board 200 (Step S108).

Similarly, the cartridge determining module M50, in the event that the cartridge detection signal CS1 is a Low signal and the cartridge detection signal CS2 is a High signal (Step S102: YES and Step S104: NO), decides that the ink cartridge is furnished with the Type A board 200 (Step S110); or in the event that the cartridge detection signal CS1 is a High signal

US 8,454,116 B2

15

and the cartridge detection signal CS2 is a Low signal (Step S102: NO and Step S104: YES), decides that the ink cartridge is furnished with the Type C board 200 described above (Step S112).

In the event that both the cartridge detection signals CS1 and CS2 are High signals Step S102: NO and Step S104: NO), the cartridge determining module M50 decides that no cartridge is attached to the selected attachment location (Step S114). In this way, the cartridge determining module M50 determines whether an ink cartridge 100 is attached, and if so what type, for each of the four attachment locations.

Remaining Ink Level Detection Process:

The remaining ink level detection process executed by the remaining ink level determining module M60 of the main control circuit 40 will now be described with reference to FIG. 11 and FIGS. 12A-C. FIG. 11 shows a flowchart depicting the processing routine of the remaining ink level detection process. FIGS. 12A-C show timing charts depicting temporal change in the shorting-detection enable signal and sensor voltage during execution of the remaining ink level detection process;

The remaining ink level determining module M60 of the main control circuit 40, in the event that the remaining ink level in the ink cartridge 100 attached at any of the attachment locations of the holder 4 is to be detected, first sets to High the short detection enable signal EN to all of the cartridge detection/short detection circuits 502 (Step S202). As a result, the short detection function is enabled in all of the cartridge detection/short detection circuits 502, and if voltage above the reference voltage V_{ref1} (6.5 V) is applied to the aforementioned terminal 520 and terminal 540, are able to output High signals as the short detection signals AB1, AB2. In other words, a state in which the short detection enable signal EN are High signals is a state in which shorting of the terminal 510 or terminal 540 to the terminal 550 or terminal 590 is monitored.

Next, the remaining ink level determining module M60 instructs the sensor driving circuit 503 to output driving voltage from the terminal 550 or terminal 590 to the sensor 104, and detect the remaining ink level output (Step S204). To describe in more specific terms, when the sensor driving circuit 503 receives an instruction signal from the remaining ink level determining module M60, the sensor driving circuit 503 outputs driving voltage from either the terminal 550 or the terminal 590, the voltage being applied to the piezoelectric element which constitutes the sensor 104 of the ink cartridge 100, charging the piezoelectric element and causing it to distort by means of the inverse piezoelectric effect. The sensor driving circuit 503 subsequently drops the applied voltage, whereupon the charge built up in the piezoelectric element is discharged, causing the piezoelectric element to vibrate. In FIG. 12, the driving voltage is the voltage shown during time interval T1. As depicted in FIG. 12, the driving voltage fluctuates between the reference voltage and the maximum voltage V_s in such a way as to describe a trapezoidal shape. The maximum voltage V_s is set to relatively high voltage (e.g. about 36 V). Via the terminal 550 of the terminal 590, the sensor driving circuit 503 detects the voltage produced by the piezoelectric effect as a result of vibration of the piezoelectric element (in FIG. 12 depicted as the voltage during time interval T2), and by measuring the vibration frequency thereof detects the remaining ink level. Specifically, this vibration frequency represents the characteristic frequency of the surrounding structures (the housing 101 and ink) that vibrate together with the piezoelectric element, and changes depending on the amount of ink remaining within the ink cartridge 100, so the remaining ink level can be detected

16

by measuring this vibration frequency. The sensor driving circuit 503 outputs the detected result to the remaining ink level determining module M60 of the main control circuit 40.

When the remaining ink level determining module M60 receives the detected result from the sensor driving circuit 503, the remaining ink level determining module M60 brings the short detection enable signal EN, which was previously set to a High signal in Step S202, back to a Low signal (Step S206), and terminates the process. In this process, the interval that the remaining ink level is being detected is a state in which the short detection enable signal EN is set to a High signal to enable short detection. In other words, remaining ink level is detected while the occurrence of shorting is being monitored by the cartridge detection/short detection circuit 502.

Process when Shorting is Detected

The process carried out in the event that, during execution of detection of the remaining ink level (Step S204), the remaining ink level determining module M60 receives a High signal as the short detection signal AB1 or AB2, e.g. shorting is detected shall be described here. In FIG. 11, a flowchart of the interrupt processing routine when shorting is detected is shown as well. When the terminal 510 or the terminal 540 shorts to the terminal that is outputting the sensor driving voltage of the terminals 550 and 590, the sensor driving voltage will be applied to the shorting terminal 510 or terminal 540. Thereupon, since the short detection enable signal EN is currently set to High, at the instant that the sensor driving voltage goes above the short detection voltage V_{ref1} (6.5 V), a High signal will be output as the short detection signals AB1, AB2 from the cartridge detection/short detection circuit 502. When the remaining ink level determining module M60 receives either of these short detection signals AB1, AB2, the remaining ink level determining module M60 suspends detection of remaining ink level, and executes the interrupt processing when shorting is detected.

When the interrupt processing is initiated, the remaining ink level determining module M60 immediately instructs the sensor driving circuit 503 to suspend the output of sensor driving voltage (Step S208).

Next, the remaining ink level determining module M60, without carrying out remaining ink level detection process to its conclusion, brings the short detection enable signal EN back to a Low signal (Step S206) to terminate the process. For example, the main control circuit 40 may take some counter-measure, such as notifying the user of the shorting.

FIG. 12A depicts change of the detection enable signal EN through time. FIG. 12B depicts sensor voltage in the event that neither the terminal 510 nor the terminal 540 is shorting to the terminal that outputs the sensor driving voltage of the terminals 550 and 590, so that the remaining ink level detection process is being executed normally. FIG. 12C depicts sensor voltage in the event that the terminal 510 or the terminal 540 is shorting to the terminal that, of the terminals 550 and 590, outputs the sensor driving voltage.

As depicted in FIG. 12A, during execution of the remaining ink level detection process, the detection enable signal EN is a High signal. As shown in FIG. 12B, in the normal state (no shorting), after high voltage V_s has been applied to the sensor 104, the applied voltage drops, and subsequently vibration voltage is produced through the piezoelectric effect. In the embodiment, V_s is set at 36 V.

As depicted in FIG. 12C, on the other hand, in the abnormal state (shorting), the sensor voltage drops at the instant that it goes above the short detection voltage V_{ref1} (6.5 V). This is due to the fact that, at the instant that the sensor voltage goes above the short detection voltage V_{ref1} (6.5 V), a High

US 8,454,116 B2

17

signal is output as the short detection signal AB1 or AB2 from the cartridge detection/short detection circuit 502 to the remaining ink level determining module M60, and the remaining ink level determining module M60 receiving this signal immediately drops the sensor driving voltage.

FIG. 13 shows an illustration of a scenario of shorting. Here, the likely scenario for shorting to other terminals by the terminals 550 and 590 which output the sensor driving voltage is, for example, the case depicted in FIG. 13, in which an electrically conductive ink drop S1 or a water drop S2 formed by condensation has become deposited on the board 200 of the ink cartridge 100, bridging the gap between the first sensor drive terminal 250 or the second sensor drive terminal 290 and another terminal or terminals on the board 200, producing shorting. For example, ink drop S1 that has adhered to the surface of the carriage 3 or ink supply needle 6 disperses and adheres as shown in FIG. 13 by the motion of attaching or detaching of ink cartridge 100. In this instance, when the ink cartridge 100 is attached, the terminal 550 that outputs the sensor driving voltage, for example, will short to another terminal 510, 520, or 560 of the carriage circuit 500 via the first sensor drive terminal 250 and the terminals (FIG. 13: terminals 210, 220, 260) bridged by the ink drop S1 to the sensor drive terminal 250. Or, the terminal 590 that outputs the sensor driving voltage will short to another terminal 540 of the carriage circuit 500 via the second sensor drive terminal 290 and the second short detection terminal 240 (FIG. 13) bridged by the water drop S2 to the second sensor drive terminal 290, for example. Such a shorting is caused by various factor as well as the adhesion of the ink drop. For example, the shorting may be caused by trapping electrically conducting object, for example, paper clip on carriage 3. The shorting also may be caused by adhesion to terminals of the electrically conducting material, for example, skin oil of user.

As mentioned previously with reference to FIG. 3, in the ink cartridge 100 pertaining to the embodiment the first sensor drive terminal 250 and the second sensor drive terminal 290 which apply the driving voltage to the sensor are arranged at the two ends of the terminal group, so the number of adjacent terminals is small. As a result, the likelihood of the first sensor drive terminal 250 and the second sensor drive terminal 290 shorting to other terminals is low.

On the board 200, if the first sensor drive terminal 250 should short to the adjacent first short detection terminal 210, the shorting will be detected by the aforementioned cartridge detection/short detection circuit 502. For example, shorting of the first sensor drive terminal 250 to another terminal caused by the ink drop S1 infiltrating from the first sensor drive terminal 250 side will be detected instantly and the output of sensor driving voltage will be suspend, preventing or reducing damage to the memory 203 and the printing apparatus 1000 circuits (the memory control circuit 501 and the cartridge detection/short detection circuit 502) caused by the shorting.

Also, the first short detection terminal 210 is adjacent to the first sensor drive terminal 250 and situated closest to the first sensor drive terminal 250. Consequently, in the event that the first sensor drive terminal 250 should short to another terminal or terminals due to the ink drop S1 or the water drop S2, there is a high likelihood that the first sensor drive terminal 250 will short to the first short detection terminal 210 as well. Consequently, shorting of the first sensor drive terminal 250 to another terminal can be detected more reliably.

In addition to detecting shorting, the first short detection terminal 210 is also used by the cartridge detection/short detection circuit 502 to determine whether an ink cartridge 100 is attached, as well as to determine the type of attached

18

ink cartridge 100. As a result, the number of terminals on the board 200 can be kept down, and it becomes possible to reduce the number of board 200 manufacturing steps and the number of parts for the board 200.

Similarly, if the second sensor drive terminal 290 should short to the second short detection terminal 240, the short will be detected by the cartridge detection/short detection circuit 502. Consequently, shorting of the second sensor drive terminal 290 to another terminal caused by the ink drop S1 or the water drop S2 infiltrating from the second sensor drive terminal 290 side can be detected instantly. As a result, damage to the circuits of the memory 203 and the printing apparatus 1000 caused by shorting can be prevented or reduced. Similarly, the second short detection terminal 240 is the terminal situated closest to the second sensor drive terminal 290. Consequently, in the event that the second sensor drive terminal 290 should short to another terminal or terminals due to the ink drop S1 or the water drop S2, there is a high likelihood that the second sensor drive terminal 290 will short to the second short detection terminal 240 as well. Consequently, shorting of the second sensor drive terminal 290 to another terminal can be detected more reliably.

The first sensor drive terminal 250 and the first short detection terminal 210 on the one hand, and the second sensor drive terminal 290 and the second short detection terminal 240 on the other, are situated at the ends of the terminal group so that the other terminals (220, 230, 260-270) lie between them. Consequently, if foreign matter (the ink drop S1, water drop S2 etc.) should infiltrate from either side as indicated by the arrows in FIG. 13, this infiltration can be detected before it infiltrates as far as the other terminals (220, 230, 260-270). Consequently, damage to the circuits of the memory 203 and the printing apparatus 1000 due to infiltration of foreign matter can be prevented or reduced.

The first sensor drive terminal 250 and the second sensor drive terminal 290 are arranged in the row on the insertion direction R side (lower row). As a result, since the terminals 250, 290 to which sensor driving voltage including high voltage is applied are situated to the back in the insertion direction, there is less likelihood that ink drops or foreign matter (e.g. a paperclip) will infiltrate to the location of these terminals 250, 290. As a result, damage to the circuits of the memory 203 and the printing apparatus 1000 caused by infiltration of foreign matter can be prevented or reduced.

The terminal group of the board 200 is arranged in a staggered pattern. As a result, unwanted contact of the terminals of the ink cartridge 100 with the terminals of the printing apparatus 1000 (the contact forming members 403, 404 mentioned previously) during the attachment operation can be prevented or reduced.

B. Variations:

Variations of the board 200 mounted to the ink cartridge 100 shall be described with reference to FIGS. 14A-16B. FIGS. 14A-D show first diagrams depicting boards pertaining to variations. FIGS. 15A-C show second diagrams depicting boards pertaining to variations. FIGS. 16A-B show third diagrams depicting boards pertaining to variations.

Variation 1:

On the board 200b depicted in FIG. 14A, the first short detection terminal 210 is similar to the first short detection terminal 210 of the board 200 of the embodiment, but has at its lower end an extended portion that reaches into proximity with the lower edge of the lower row. The extended portion is positioned between the first sensor drive terminal 250 and the reset terminal 260 of the lower row. As a result, for example, even in the event of adhesion of an ink drop S3 as depicted in FIG. 14(a), shorting of the extended portion of the short

detection terminal **210** to the first sensor drive terminal **250** will be detected. Like this, when the first sensor drive terminal **250** and terminal other than the first short detection terminal **210** are shorting, there is a high possibility that the first sensor drive terminal **250** and the first short detection terminal **210** are shorting and the sensor driving voltage is suspended. Accordingly, problems caused by shorting of the first sensor drive terminal **250** to another terminal (in the example of FIG. **14A**, the reset terminal **260**) can be prevented or reduced.

As shown in FIG. **14A**, the second short detection terminal **240** of the board **200b** is also similar in shape to the first short detection terminal **210** mentioned above, and shorting of the second sensor drive terminal **290** to another terminal will also be detected more reliably.

Variation 2:

The board **200c** depicted in FIG. **14B** has, in addition to the arrangement of the board **200b** described above, also has an extended portion located at the upper side of the first sensor drive terminal **250**, and reaching into proximity with the upper edge of the upper row. As a result, even in the event of adhesion of an ink drop **S4** as depicted in FIG. **14(b)**, shorting of the short detection terminal **210** to the extended portion of the first sensor drive terminal **250** will be detected. Like this, when the first sensor drive terminal **250** and terminal other than the first short detection terminal **210** are shorting, there is a high possibility that the first sensor drive terminal **250** and the first short detection terminal **210** are shorting and the sensor driving voltage is suspended. Accordingly, problems caused by shorting of the first sensor drive terminal **250** to another terminal can be prevented or reduced.

As shown in FIG. **14B**, the second sensor drive terminal **290** of the board **200c** is also similar in shape to the first sensor drive terminal **250** mentioned above, and infiltration of an ink drop from the end, at the end at which the second sensor drive terminal **290** is situated, can be detected instantly.

Variation 3:

The board **200d** depicted in FIG. **14C** differs from the board **200** of the embodiment in that there is no second short detection terminal **240**. In the case of the Type A board **200** depicted in FIG. **10A**, the second short detection terminal **240** does not carry out detection of contact by means of the cartridge detection/short detection circuit **502** (since there is no shorting to the ground terminal **220**). Consequently, in the case of the Type A board **200**, the second short detection terminal **240** is used for short detection only and accordingly can be dispensed with. In this case as well, since the first short detection terminal **210** is at the location closest to the first sensor drive terminal **250**, when the first sensor drive terminal **250** and terminal other than the first short detection terminal **210** are shorting, there is a high possibility that the first sensor drive terminal **250** and the first short detection terminal **210** are shorting and the sensor driving voltage is suspended. Infiltration of an ink drop to second sensor drive terminal **290** side will also be detected to a certain extent. In FIG. **14C**, the symbol CP represents the location of contact with the contact forming member **403** that would contact the second short detection terminal **240** if the second short detection terminal **240** were present (i.e. the contact forming member **403** corresponding to the terminal **540** of the carriage circuit **500**). Even in the case that the second short detection terminal **240** is absent, if a shorting should occur between the second sensor drive terminal **290** and the contact forming member **403** corresponding to the terminal **540** of the carriage circuit **500** due to an ink drop **S5**, infiltration of the ink drop **S5** will be detected. Similarly, in the case of a Type C board **200**, the first short detection terminal **210** may be dispensed with.

Variation 4:

On the board **200e** depicted in FIG. **14D**, the first sensor drive terminal **250** and the first short detection terminal **210** have elongated shape reaching from the vicinity of the upper edge of the upper row to the vicinity of the lower edge of the lower row. The terminals of this shape, as the contact locations are indicated by the symbol CP in FIG. **14D**, can contact the corresponding contact forming portions **403** arranged in a staggered pattern. In the case of the board **200e**, like the board **200c** described previously, even if an ink drop **S6** should become deposited for example, shorting between the extended portions of the first short detection terminal **210** and the first sensor drive terminal **250** will be detected. Like this, first short detection terminal **210** is located between first sensor drive terminal **250** and terminal other than the first short detection terminal **210**. Accordingly, when the first sensor drive terminal **250** and terminal other than the first short detection terminal **210** are shorting, there is a high possibility that the first sensor drive terminal **250** and the first short detection terminal **210** are shorting and the sensor driving voltage is suspended.

The second sensor drive terminal **290** and the second short detection terminal **240** of the board **200e** have shape similar to the first sensor drive terminal **250** and the first short detection terminal **210** described above. Accordingly, when the second sensor drive terminal **290** and terminal other than the second short detection terminal **240** are shorting, there is a high possibility that the second sensor drive terminal **290** and the second short detection terminal **240** are shorting. As a result, the possibility preventing or reducing the problems caused by shorting of the sensor drive terminal **250**, **290** to another terminal becomes higher.

Variation 5:

On the board **200f** depicted in FIG. **15A**, the terminal which corresponds to the first short detection terminal **210** and the ground terminal **220** in the board **200** pertaining to the embodiment is an integral terminal **215** wherein these two terminals are integrally formed as a single member. This board **200f** can be used in place of the Type A or Type B board **200** (FIG. **10**) whose first short detection terminal **210** and ground terminal **220** are shorted. With the board **200f**, the need is obviated for a line between the first short detection terminal **210** and the ground terminal **220**, which was required in the case of in the board **200** pertaining to the embodiment, so the board **200** requires fewer process steps and fewer parts.

Variation 6:

On the board **200g** depicted in FIG. **15B**, the terminals **210-240** of the upper row each have shape similar to the first short detection terminal **210** of the board **200b** described previously. Specifically, each of the terminals **210-240** has an extended portion situated at the lower edge of the corresponding terminal of the board **200** pertaining to the embodiment and reaching into proximity with the lower edge of the lower row. The terminals **250-290** of the lower row of the board **200g** are similar in shape to the first sensor drive terminal **250** of the board **200c** described earlier. Specifically, the each of the terminals **250-290** has an extended portion situated at the upper edge of the corresponding terminal of the board **200** pertaining to the embodiment and reaching into proximity with the upper edge of the upper row.

As a result, the terminals **210-290** of the board **200g** are arranged so as to form a terminal group composed of a single row of terminals of generally oar shape of in mutually different arrangement, rather than being arranged in two rows. The first sensor drive terminal **250** and the second sensor drive terminal **290** to which the high-voltage sensor driving voltage is applied are positioned at the two ends of the single row of

US 8,454,116 B2

21

the terminal group, with the first short detection terminal **210** and the second short detection terminal **240** respectively arranged adjacently inward from the first sensor drive terminal **250** and the second sensor drive terminal **290**.

With the board **200g**, an ink drop or foreign matter infiltrating from either end can be detected immediately at the point in time that shorting occurs between the first sensor drive terminal **250** and the short detection terminal **210**, or between the second sensor drive terminal **290** and the second short detection terminal **240**. In the event that the first sensor drive terminal **250** or the second sensor drive terminal **290** should short to another terminal, in the case where the shorting is due to an ink drop or the like, the likelihood is extremely high that shorting between the first sensor drive terminal **250** and the short detection terminal **210**, or between the second sensor drive terminal **290** and the second short detection terminal **240**, will occur at the same time. Consequently, shorting of the first sensor drive terminal **250** or the second sensor drive terminal **290** to another terminal can be detected reliably. As a result, damage to the memory **203** and the printing apparatus **1000** circuits (the memory control circuit **501** and the cartridge detection/short detection circuit **502**) caused by the shorting can be prevented or minimized.

Variation 7:

On the board **200h** depicted in FIG. **15C**, the terminals **210-290** have elongated shape extending over a distance equivalent to two rows of the board **200** pertaining to the embodiment, in a manner similar to the first sensor drive terminal **250** and the first short detection terminal **210** of the board **200e** described previously. The terminals of this shape, as the contact locations are indicated by the symbol **cp** in FIG. **15C**, can contact the corresponding contact forming portions **403** arranged in a staggered pattern.

In the board **200h**, the terminals **210-290** are arranged so as to form a single row in the orthogonal direction to the insertion direction **R**, in a manner similar to the board **200g** described above. Also, like the board **200g**, the first sensor drive terminal **250** and the second sensor drive terminal **290** to which the high-voltage sensor driving voltage is applied are positioned at the two ends of the single row of terminals, with the first short detection terminal **210** and the second short detection terminal **240** respectively arranged adjacently inward from the first sensor drive terminal **250** and the second sensor drive terminal **290**. As a result, the board **200h** affords advantages analogous to those of the board **200g** described above.

Variation 8:

The first short detection terminal **210** of the board **200i** depicted in FIG. **16A** has a shape that is longer on the left side in the drawing, as compared to the first short detection terminal **210** of the board **200** pertaining to the embodiment. Additionally, the first short detection terminal **210** of the board **200i** has an extended portion reaching from the left edge portion to the vicinity of the lower edge of the lower row. The extended portion is situated to the left of the first sensor drive terminal **250** in the lower row. In other words, the extended portion is disposed to further from the middle of the terminal group in a direction substantially orthogonal to the insertion direction **R** than the first sensor drive terminal **250**. In this case, whereas viewed in terms of the terminal as a whole, the first short detection terminal **210** is situated outwardly (to the left side) of the first sensor drive terminal **250**, when viewed in terms of the contact portion **CP** of the terminal, of the contact portions **CP** of all of the terminals **210-290** the contact portion **CP** of the first sensor drive terminal **250** is the one situated at the outermost position (left side), in the same manner as in the embodiment. Also, shorting between the first

22

sensor drive terminal **250** and the first short detection terminal **210** that includes the contact portion **CP** adjacent to the contact portion **CP** of the first sensor drive terminal **250** is detected. Accordingly, the board **200i** pertaining to this variation affords advantages similar to the board **200** pertaining to the embodiment. Specifically, infiltration of an ink drop from the edge can be detected instantly, and damage to the circuits of the memory **203** and the printing apparatus **1000** can be prevented or minimized. Additionally, since the first short detection terminal **210** has the extended portion, the length of a first portion that is a portion adjacent to the circumferential edge of the first short detection terminal **210** among the circumferential edge of the first sensor drive terminal **250** becomes long. As shown in FIG. **16B**, the length of the first portion is longer than that of a second portion that is a portion adjacent to the circumferential edge of the reset terminal **260** among the among the circumferential edge of the first sensor drive terminal **250**. As a result, when the first sensor drive terminal **250** and terminal other than the first short detection terminal **210**, for example, the reset terminal **260** are shorting, there is a high possibility that the first sensor drive terminal **250** and the first short detection terminal **210** are shorting. Accordingly, the sensor driving voltage is suspended and problems caused by shorting of the first sensor drive terminal **250** to another terminal can be prevented or reduced with higher probability.

The first short detection terminal **210** of the board **200p** in FIG. **16C** has the longer extended portion than the first short detection terminal **210** of the board **200i**. As shown in FIG. **16C**, the extended portion of the first short detection terminal **210** of the board **200p** extends from upper left to lower right of the first sensor drive terminal **250** along the circumferential edge of the first sensor drive terminal **250**. As a result, the length of the first portion in the board **200p** is longer than that in the board **200i**. Accordingly, when the first sensor drive terminal **250** and terminal other than the first short detection terminal **210** are shorting, there is a higher possibility the sensor driving voltage is suspended and problems caused by shorting of the first sensor drive terminal **250** to another terminal can be prevented or reduced.

The first short detection terminal **210** of the board **200q** in FIG. **16D** has the longer extended portion than the first short detection terminal **210** of the board **200i** and **200p**. As shown in FIG. **16D**, the extended portion of the first short detection terminal **210** of the board **200q** extends from upper left through lower to upper right of the first sensor drive terminal **250** along the circumferential edge of the first sensor drive terminal **250**. In other words, the first short detection terminal **210** is formed so as to surround the first sensor drive terminal **250** completely. As a result, the length of the first portion in the board **200q** is longer than that in the board **200i** and **200p**. Accordingly, when the first sensor drive terminal **250** and terminal other than the first short detection terminal **210** are shorting, there is a higher possibility the sensor driving voltage is suspended and problems caused by shorting of the first sensor drive terminal **250** to another terminal can be prevented or reduced.

As shown in FIGS. **16A-C**, board **200i**, **200p**, **200q** are added the direction in which the portion of the first short detection terminal **210** is located adjacently to a portion of the sensor drive terminal **250** by providing the extended portion of the first short detection terminal **210**. About board **200i**, the extended portion of the first short detection terminal **210** located adjacently to left border of the first sensor drive terminal **250** in a lateral direction towards an edge of the ink cartridge **100**, and the first short detection terminal **210** itself is located adjacently to upper border of the first sensor drive

terminal **250** in opposite direction of the insertion direction R. Meanwhile, about board **200p**, in addition to above-mentioned two directions, the extended portion of the first short detection terminal **210** is located adjacently to lower border of the first sensor drive terminal **250** in the insertion direction R. Furthermore, about board **200q**, the extended portion of the first short detection terminal **210** is located adjacently to right border of the first sensor drive terminal **250** in lateral direction away from an edge of the ink cartridge **100**. In other words, about board **200q**, at least a portion of the first short detection terminal **210** is located adjacently to the first sensor drive terminal **250** in all direction.

When the first sensor drive terminal **250** and terminal other than the first short detection terminal **210** are shorting by ink drop or other object infiltrating from the direction in which the portion of the first short detection terminal **210** is located adjacently to the portion of the first sensor drive terminal **250**, there is a much high possibility that the first sensor drive terminal **250** and the first short detection terminal **210** are shorting. Accordingly, problems caused by shorting of the first sensor drive terminal **250** to another terminal by ink drop or other object infiltrating from such direction can be prevented or reduced with much high probability. In the present variations, the extended portion of the first short detection terminal **210** adds the direction in which the first short detection terminal **210** and the first sensor drive terminal **250** are adjacent each other, and prevents or reduces problems caused by shorting of the first sensor drive terminal **250** to another terminal with much high probability.

In the boards **200i**, **200p**, **200q** pertaining to this variation, only the first short detection terminal **210** on the left side is furnished with a structure having the extended portion described above, but it would be possible to furnish the second short detection terminal **240** on the right side with a structure having an extended portion, in addition to the first short detection terminal **210** or instead of the first short detection terminal **210**. In this case as well, there are afforded advantages analogous to those of the boards **200i**, **200p**, **200q** pertaining to this variation.

Variation 9:

The board **200j** depicted in FIG. 16B, like the board **200f** described previously in Variation 5, has an integral terminal **215** wherein the first short detection terminal **210** and the ground terminal **220** in the board **200** pertaining to the embodiment are integrally formed as a single member. The integral terminal **215** of the board **200j** differs in shape from the integral terminal **215** of the board **200f** described previously. Specifically, the integral terminal **215** of the board **200j**, like the first short detection terminal **210** of the board **200f** described in Variation 8, has a shape elongated on the left side, and has an extended portion reaching from the left edge portion to the vicinity of the lower edge of the lower row. In this case, advantages analogous to those of the board **200f** pertaining to Variation 8 are attained, while reducing the number of production steps and parts needed for the board.

In the embodiment and variations described hereinabove, all of the terminals are situated on the board **200**, but it is not necessary that all terminals be situated on the board **200**. For example, it would be acceptable for some of the terminals to be situated on the housing **101** of the ink cartridge **100**. By way of specific examples, Variation 10 and Variation 11 shall be described below with reference to FIGS. 17A-18D. FIGS. 17A-D show diagrams depicting the construction around boards of ink cartridges pertaining to variations. FIGS. 18A-D show cross sections A-A to D-D in FIG. 17.

Variation 10:

The board **200k** depicted in FIG. 17A is furnished with seven terminals **210-240** and **260-280**, out of the nine terminals **210-290** furnished to the board **200** of the embodiment. Out of the nine terminals **210-290** furnished to the board **200** of the embodiment, the board **200k** lacks the first sensor drive terminal **250** and the second sensor drive terminal **290**. The board **200k** pertaining to this variation is furnished with notches NT1 or NT2 situated in zones that include the locations where the first sensor drive terminal **250** and the second sensor drive terminal **290** were disposed on the board **200** pertaining to the embodiment. The notches may have the shape indicated by the solid lines NT1, or the shape indicated by the broken lines NT2, in FIG. 17A. Terminals **150** and **190** having function similar to the first sensor drive terminal **250** and the second sensor drive terminal **290** of the board **200** in the embodiment are arranged on the housing **101** situated to the rear of the board **200k**. Naturally, with the ink cartridge **100** attached to the holder **4**, these terminals **150** and **190** are situated at locations contacting the corresponding apparatus-side terminals **450** and **490**.

A-A cross section viewed in FIG. 17A is depicted in FIG. 18A. As shown in FIG. 18A, a depressed portion DE, formed by a gap between the notch NT1 of the board **200k** and the terminal **150**, is situated between the terminal **150** and the adjacent terminals **260**, **210** (in FIG. 18A, the reset terminal **260** is shown). While omitted from the drawing, a similar depressed portion DE is situated between the terminal **190** and the adjacent terminals **280**, **240**.

According to this variation, the following advantages are afforded in addition to those analogous to the board **200** pertaining to the embodiment. If an ink drop or foreign matter should infiltrate from the end of the ink cartridge **100** pertaining to this variation, it will become trapped in the depressed portion DE arranged surrounding the terminal **150** or the terminal **190**, whereby shorting of the terminal **150** or the terminal **190** to another terminal due to an infiltrating ink drop or foreign matter can be further prevented or minimized.

Variation 11:

The board **200m** depicted in FIG. 17B, rather than having the notches NT1 or NT2 pertaining to Variation 10, is instead furnished with through-holes HL situated at locations corresponding to the locations where the first sensor drive terminal **250** and the second sensor drive terminal **290** are situated on the board **200** pertaining to the embodiment. B-B cross section viewed in FIG. 17B is depicted in FIG. 18B. Other arrangements of the ink cartridge **100** pertaining to Variation 11 are the same as those of the ink cartridge **100** pertaining to Variation 10. In this variation as well, depressed portions DE are situated between the terminals **150**, **190** and the adjacent terminals. Accordingly, the ink cartridge **100** pertaining to this variation affords advantages analogous to those of the ink cartridge **100** pertaining to Variation 10.

Variation 12:

In the boards pertaining to the embodiment and variations, all terminals are connected to one of memory **203** and sensor **104**. However, the board may include dummy terminal that is not connected to any device. An example of such type of the board will be described as Variation 12 with reference to FIGS. 19A-D. FIGS. 19A-D show fourth diagrams depicting boards pertaining to variations.

The board **200r** includes the upper row formed by four terminals and the lower row formed by five terminals, as with the board **200** pertaining to the embodiment. Arrangement and function of the terminals **210-290** forming the upper row and the lower row of board **200r** is the same as those of the terminals of board **200** in the embodiment, so the detailed description thereof is omitted.

US 8,454,116 B2

25

The board **200r** shown in FIG. **19A** has the dummy terminals DT between the upper row and the lower row and on the underside (the insertion direction side) of the lower row. The dummy terminals DT, for example, are made of the same material as other terminal **210-290**. FIG. **19C** shows E-E cross-section including dummy terminals DT. The dummy terminals DT has about the same thickness as other terminal **210-290**.

The dummy terminals DT are for scraping away foreign object adherent on the contact forming members **403**, for example, dust when ink cartridge **100** is attached or detached. This enables to prevent foreign object from being brought to the terminal to be contacted by contact forming member **403** (for example, the first sensor drive terminal **250** in FIG. **19C**) when ink cartridge **100** is attached or detached, and to prevent contact failure between the terminal and the contact forming member **403**.

The board **200r** shown in FIG. **19A** has the dummy terminal DT between the first sensor drive terminal **250** and the short detection terminal **210**, so you can't say first sensor drive terminal **250** is located adjacent to first short detection terminal **210**. However, the dummy terminals DT is not connected to memory **203** and not connected to the apparatus-side terminals **510-590** on printing apparatus **1000**. Therefore, the shorting between the first sensor drive terminal **250** and the dummy terminals DT never cause any problem. Accordingly, the board **200r** can afford working effects analogous to the board **200** pertaining to the embodiment. That is to say, about the board **200r**, even if first sensor drive terminal **250** is not located adjacent to first short detection terminal **210** in a precise sense, at least a portion of the first short detection terminal **210** is arranged relative to at least a portion of the first sensor drive terminal **250**, without a terminal connected to memory **203** (terminal **220, 230, 260-280**) therebetween in at least one direction, for the detection of shorting between the first sensor drive terminal **250** and the first short detection terminal **210**. In such a case, the first sensor drive terminal **250** is substantially located adjacent to first short detection terminal **210**. Consequently, in the event that the first sensor drive terminal **250** should short to another terminal or terminals due to the ink drop or the water drop, there is a high likelihood that the first sensor drive terminal **250** will short to the short detection terminal **210** as well. As a result, the output of sensor driving voltage is suspend and damage to the circuits of the memory **203** and the printing apparatus **1000** caused by shorting can be prevented or reduced.

Variation 13:

The boards pertaining to the embodiment and variations, as shown in FIG. **2**, are described as the board mounted on an ink cartridge **100** used for "on carriage" type printer. However, the boards pertaining to the embodiment and variations may be mounted on an ink cartridge used for "off carriage" type printer. The ink cartridge used for "off carriage" type printer will be described below with reference to FIG. **20** and FIG. **21**. FIG. **20** shows a perspective view of the construction of the ink cartridge pertaining to the variation 13. FIG. **21** shows a picture of the ink cartridge pertaining to the variation 13 being attached to the printer.

Ink cartridge **100b** pertaining to Variation 13 is configured for installation in an "off carriage" type printer, i.e., one in which the ink cartridge is not installed on a carriage. Off carriage type printers are typically large-scale printers; the ink cartridges employed in such large-scale printers are typically larger in size than the ink cartridges employed in on-carriage type printers.

26

Ink cartridge **100b** comprises a housing **1001** containing ink, a board mounting portion **1050** for mounting board **200**, an ink feed orifice **1020** for supplying ink from a housing **1001** to the printer; an air feed orifice **1030** allowing intake of air into ink cartridge **100b** to allow smooth flow of ink; and guide portions **1040** for installation in the printer. The exterior dimensions of ink cartridge **100b** are such that the side thereof (i.e. the depth direction) extending perpendicular to the side on which the guide portions **1040**, etc. are formed (i.e. the width direction) is longer than the width direction. The relationship of the depth-wise dimension to the width-wise dimension of board **200**, expressed as a ratio of the two, is 15:1 or greater, for example.

As in the case of the above-mentioned embodiment, board **200** is positioned by means of boss hole **202** and boss slot **201**, and secured on the board mounting portion **1050** of ink cartridge **100b**.

As shown in FIG. **21**, when installing the ink cartridge **100b** in the printer, the guide portions **1040** of ink cartridge **100b** guide the guide pins **2040** on the printer so that the board mounting portion **1050**, ink feed orifice **1020**, and air feed orifice **1030** are appropriately contacted/coupled with a contact pin **2050**, ink feed orifice **2020**, and air feed orifice **2030** on the printer. The insertion direction of ink cartridge **100b** is indicated by arrow R in FIG. **21**. The insertion direction R on board **200** in this variation is the same as that in the above-mentioned embodiment.

Ink cartridge **100b** used for off carriage type printer pertaining to this variation can prevent or reduce problems caused by shorting of the first sensor drive terminal **250** to another terminal as in the case of the embodiment and variations described above.

Variation 14:

Configuration of the ink cartridge for "on carriage" type printer shown in FIG. **2** is one example among many. Configuration of the ink cartridge for "on carriage" type printer is not limited to this. Other configuration of the ink cartridge for "on carriage" type printer shall be described as Variation 14 with reference to FIGS. **22-24**. FIG. **22** shows a first diagram of the construction of the ink cartridge pertaining to Variation 14. FIG. **23** shows a second diagram of the construction of the ink cartridge pertaining to variation 14. FIG. **24** shows a third diagram of the construction of the ink cartridge pertaining to Variation 14.

As shown in FIGS. **22** and **23**, the ink cartridge **100b** pertaining to Variation 14 includes housing **101b**, board **200** and sensor **104b**. On the bottom face of the housing **101b**, as with ink cartridge **100** in the embodiment, there is formed an ink supply orifice **110b** into which the ink supply needle inserts when ink cartridge **100b** is attached to the holder **4b**. The board **200** is mounted on the lower side (Z-axis plus direction side) of the front face (Y-axis plus direction side face) of the housing **101** as with ink cartridge **100** in the embodiment. Configuration of the board **200** is identical with the board **200** in the embodiment. The sensor **104b** is embedded in the side wall of the housing **101b** and used for detection of remaining ink level. Hook **120b** that engages with catching part of the holder **4b** when the ink cartridge **100b** is attached to the holder **4b** is mounted on the upper side of the front face of the housing **101b**. Hook **120b** fixates the Ink cartridge **100b** to the holder **4b**. The insertion direction when the ink cartridge **100b** is attached to the holder **4b** is a direction of arrow R in FIG. **22** (Z-axis plus direction) as with the ink cartridge **100** in the embodiment.

The housing **101b** has displacement preventers PO1-PO4 on the side portion (x-axis direction side) of housing **101b** close to the board **200**. The displacement preventers PO1-

PO4 comes into contact with or close to a corresponding portion of the side wall of the holder 4b when the ink cartridge 100b is attached to the holder 4b. This prevents the ink cartridge 100b from moving in X-axial direction from its ideal position on the holder 4b. Specifically, the displacement preventers PO1 and PO2 are located on the upper side of the board 200 and prevent the upper side of the 100b from swinging in X-axial direction taking the ink supply orifice 110b as an axis of rotation. The displacement preventers PO3 and PO4 are lateral to the terminals 210-290 on the board 200 (FIG. 3) and keep the terminals 210-290 in the correct position so as to contact the corresponding apparatus-side terminal 410-490 correctly.

The electrical arrangements of the ink cartridge 100b pertaining to Variation 14 is identical with those of the ink cartridge 100 pertaining to above-embodiment described with reference to FIG. 7. So, the description thereof is omitted.

The ink cartridge 100b pertaining to Variation 14 affords the following working effects in addition to the same working effects as the ink cartridge 100 pertaining to the embodiment. Since the ink cartridge 100b has the displacement preventers PO1-PO4, it can prevent or reduce the position displacement when the ink cartridge 100b is attached to the holder 4b. Especially, since the displacement preventers PO3 and PO4 are lateral to the terminals 210-290 on the board 200, accuracy of positioning of the terminals 210-290 relative to the corresponding apparatus-side terminals can be improved. Further, as described with reference to FIG. 3, in the board 200, the sensor drive terminal 250 and the second sensor drive terminal 290 are arranged at each end of the terminals 210-290, that is, the sensor drive terminal 250 and the second sensor drive terminal 290 are closest to the displacement preventers PO4 and PO4 respectively. This lead to improvement of accuracy of positioning of the sensor drive terminal 250 and the second sensor drive terminal 290. Therefore, the false contact between the terminals 250, 290 to which high voltage is applied and one of the non-corresponding apparatus-side terminals can be prevented or reduced.

As substitute for the board 200 in the embodiment, one of the boards 200b-200s shown in FIGS. 14-19 can be mounted on the ink cartridge 100b shown in FIG. 22-24.

Other Variations:

As depicted in FIGS. 17C-D and in FIGS. 18C-D, porous elements PO may be disposed within the depressed portions DE in Variation 10 and Variation 11 described above, i.e. between the terminals 150, 190 and the board. By so doing, ink drops or condensed water, which can easily cause shorting of the terminals 150, 190 to other terminals, can be effectively absorbed by the porous elements PO. Accordingly, this design also affords advantages analogous to those of Variation 10 and Variation 11 discussed above.

In the embodiment herein, the ink cartridge 100 is furnished with a sensor 104 (piezoelectric element) and memory 203 as the plurality of the devices; however, the plurality of the devices are not limited to a sensor 104 and memory 203. For example, the sensor 104 may be a sensor of a type that detects the properties or level of ink by means of applying voltage to the ink within an ink cartridge 100, and measuring its resistance. In the embodiment, among the plurality of the devices, the sensor 104 is mounted on the housing 101 and the memory 203 is mounted on the board 200. However, the arrangements of the plurality of the devices are not limited to those in the embodiment. For example, the memory 203 and the board 200 may be separate, and the memory 203 and the board 200 may be installed on the housing 101 individually. The plurality of the devices may be integrated into a circuit board or a single module. The circuit board or the single

module may be mounted on the housing 101 or the board 200. It's preferred that terminals connected to a device to which relatively high voltage among the plurality of the devices are arranged in positions of the first sensor drive terminal 250 and the second sensor drive terminal 290 described above, and terminals connected to a device to which relatively low voltage among the plurality of the devices are arranged in positions of the terminals 220, 230, 260-280. In this case, damage to the ink cartridge 100 and the printing apparatus 1000 caused by shorting between the terminal connected to the device to which relatively high voltage and the terminal connected to the device to which relatively low voltage can be prevented or reduced.

In above-mentioned embodiment, five terminals for memory 203 (220, 230, 260-280) and two terminals for sensor 104 (250, 290) are employed, however, other number of terminals may be employed due to the specification of the device. For example, the terminal connected to the device to which relatively high voltage may be one. In this case, such terminal may be arranged in a position of any of the terminals 250, 290 described above.

Whereas in the embodiment herein the invention is implemented in an ink cartridge 100, implementation thereof is not limited to ink cartridges, with implementation in a similar manner to receptacles containing other types of printing material, such as toner, being possible as well.

With regard to the arrangements of the main control circuit 40 and the carriage circuit 500 in the printing apparatus, portions of these arrangements implemented through hardware could instead be implemented through software, and conversely portions implemented through software could instead be implemented through hardware.

While the printing material container and board pertaining to the invention have been shown and described on the basis of the embodiment and variation, the embodiments of the invention described herein are merely intended to facilitate understanding of the invention, and implies no limitation thereof. Various modifications and improvements of the invention are possible without departing from the spirit and scope thereof as recited in the appended claims, and these will naturally be included as equivalents in the invention.

What is claimed is:

1. An ink cartridge for mounting on an ink jet printing apparatus, the ink jet printing apparatus having a print head and a plurality of apparatus-side contact forming members, the ink cartridge comprising:

a body;

an ink supply opening having an exit on an exterior portion of the body, adapted to supply ink from the ink cartridge to the printing apparatus;

a memory device adapted to be driven by a memory driving voltage;

an electronic device adapted to receive a voltage higher than the memory driving voltage; and

a plurality of terminals having contact portions adapted and positioned to contact corresponding apparatus-side contact forming members so that electrical communication is enabled with the ink jet printing apparatus, the contact portions of the terminals including a plurality of memory contact portions electrically coupled to the memory device, a first electronic device contact portion electrically coupled to the electronic device, a second electronic device contact portion electrically coupled to the electronic device, and a short detection contact portion positioned and arranged to electrically contact a

US 8,454,116 B2

29

contact forming member that itself is electrically coupled to a short detection circuit of the printing apparatus, wherein:

the contact portions are arranged so that, when the terminal arrangement is viewed from the vantage of the contact forming members, with the terminals oriented as if in contact with the contact forming members so that electrical communication is enabled with the ink jet printing apparatus, and with the ink cartridge oriented with the exit of the ink supply opening facing downwards, the contact portion farthest to the left is the first electronic device contact portion, the contact portion that is farthest to the right is the second electronic device contact portion, the contact portion that is second farthest to the right is the short detection contact portion, and the memory contact portions are located to the left of the short detection contact portion and to the right of the first electronic device contact portion.

2. The ink cartridge of claim 1, wherein the short detection contact portion is positioned and adapted for detecting a short between the short detection contact portion and at least the second electronic device contact portion, the short detection contact portion being adjacent to the second electronic device contact portion, with no other contact portion therebetween.

3. The ink cartridge of claim 1, wherein the electronic device is adapted to receive a first voltage and output a voltage lower than the first voltage.

4. The ink cartridge of claim 1, and including a second short detection contact portion arranged so that the second short detection contact portion is the second farthest of the contact portions to the left.

5. The ink cartridge of claim 4, wherein the memory contact portions are to the left of the short detection contact portion and the second electronic device contact portion and to the right of the second short detection contact portion and the first electronic device contact portion.

6. The ink cartridge of claim 1, wherein the number of contact portions adjacent to the second electronic device contact portion is smaller than the number of contact portions adjacent to the short detection contact portion.

7. The ink cartridge of claim 1, wherein the contact portions are arranged in a first row of contact portions and in a second row of contact portions such that the first row of contact portions is below the second row of contact portions, and the first electronic device contact portion and the second electronic device contact portion are located at the ends of the first row of contact portions.

8. The ink cartridge of claim 1, wherein the contact portions are arranged in a first row of contact portions and in a second row of contact portions, the first row of contact portions and the second row of contact portions extend in a row direction which is generally orthogonal to an insertion direction in which the ink cartridge is mounted into the ink jet printing apparatus,

the first row of contact portions is disposed at a location that is further in the insertion direction than the second row of contact portions, and

the first electronic device contact portion and the second electronic device contact portion are located at the ends of the first row of contact portions.

9. An ink cartridge for mounting on an ink jet printing apparatus, the ink jet printing apparatus having a print head

30

and a plurality of apparatus-side contact forming members, the ink cartridge comprising:

a body;

an ink supply opening having an exit on an exterior portion of the body, adapted to supply ink from the ink cartridge to the printing apparatus;

a low voltage electronic device;

a high voltage electronic device; and

a plurality of terminals having contact portions adapted and positioned to contact corresponding apparatus-side contact forming members so that electrical communication is enabled with the ink jet printing apparatus, the contact portions of the terminals including a plurality of low voltage electronic device contact portions electrically coupled to the low voltage electronic device, a first high voltage electronic device contact portion electrically coupled to the high voltage electronic device, a second high voltage electronic device contact portion electrically coupled to the high voltage electronic device and arranged to have applied thereto a higher voltage than the low voltage electronic device contact portions, and a short detection contact portion positioned and arranged to electrically contact a contact forming member that itself is electrically coupled to a short detection circuit of the printing apparatus, wherein:

the contact portions are arranged so that, when the terminal arrangement is viewed from the vantage of the contact forming members, with the terminals oriented as if in contact with the contact forming members so that electrical communication is enabled with the ink jet printing apparatus, and from the perspective with the ink cartridge oriented with the exit of the ink supply opening facing downwards, the contact portion farthest to the left is the first high voltage electronic device contact portion, the contact portion that is farthest to the right is the second high voltage electronic device contact portion, the contact portion that is second farthest to the right is the short detection contact portion, and the low voltage electronic device contact portions are located to the left of the short detection contact portion and to the right of the first high voltage electronic device contact portion.

10. The ink cartridge of claim 9, wherein the low voltage electronic device is a memory.

11. The ink cartridge of claim 9, wherein the short detection contact portion is positioned and adapted for detecting a short between the short detection contact portion and at least the second electronic device contact portion, the short detection contact portion being adjacent to the second electronic device contact portion, with no other contact portion therebetween.

12. The ink cartridge of claim 9, wherein the high voltage electronic device is adapted to receive a first voltage and output a voltage lower than the first voltage.

13. The ink cartridge of claim 9, and including a second short detection contact portion arranged so that the second short detection contact portion is the second farthest of the contact portions to the left.

14. The ink cartridge of claim 13, wherein the low voltage electronic device contact portions are to the left of the short detection contact portion and the second high voltage electronic device contact portion and to the right of the second short detection contact portion and the first high voltage electronic device contact portion.

15. The ink cartridge of claim 9, wherein the number of contact portions adjacent to the second high voltage elec-

US 8,454,116 B2

31

tronic device contact portion is smaller than the number of contact portions adjacent to the short detection contact portion.

16. The ink cartridge of claim 9, wherein the contact portions are arranged in a first row of contact portions and in a second row of contact portions such that the first row of contact portions is below the second row of contact portions, and the first high voltage electronic device contact portion and the second high voltage electronic device contact portion are located at the ends of the first row of contact portions.

17. The ink cartridge of claim 9, wherein: the contact portions are arranged in a first row of contact portions and in a second row of contact portions, the first row of contact portions and the second row of contact portions extend in a row direction which is generally orthogonal to an insertion direction in which the ink cartridge is mounted into the ink jet printing apparatus, the first row of contact portions is disposed at a location that is further in the insertion direction than the second row of contact portions, and the first high voltage electronic device contact portion and the second high voltage electronic device contact portion are located at the ends of the first row of contact portions.

18. A circuit board mountable on a printing material container that is used in an ink jet printing apparatus, the ink jet printing apparatus having a print head and a plurality of apparatus-side contact forming members, the printing material container having a body and an ink supply opening, the ink supply opening having an exit on an exterior portion of the body and being adapted to supply ink from the printing material container to the printing apparatus, the circuit board comprising:

- a memory device adapted to be driven by a memory driving voltage;
- an electronic device adapted to receive a voltage higher than the memory driving voltage; and
- a plurality of terminals having contact portions adapted and positioned to contact corresponding apparatus-side contact forming members so that electrical communication is enabled with the ink jet printing apparatus, the contact portions of the terminals including a plurality of memory contact portions electrically coupled to the memory device, a first electronic device contact portion electrically coupled to the electronic device, a second electronic device contact portion electrically coupled to the electronic device, and a short detection contact portion positioned and arranged to electrically contact a contact forming member that itself is electrically coupled to a short detection circuit of the printing apparatus, wherein:

the contact portions are arranged so that, when the terminal arrangement is viewed from the vantage of the contact forming members, with the terminals oriented as if in contact with the contact forming members so that electrical communication is enabled with the ink jet printing apparatus, and with the ink cartridge oriented with the exit of the ink supply opening facing downwards, the contact portion farthest to the left is the first electronic device contact portion, the contact portion that is farthest to the right is the second electronic device contact portion, the contact portion that is second farthest to the right is the short detection contact portion, and the memory contact portions are located to the left of the

32

short detection contact portion and to the right of the first electronic device contact portion.

19. The circuit board of claim 18, wherein the electronic device is adapted to receive a first voltage and output a voltage lower than the first voltage.

20. The circuit board of claim 18, and including a second short detection contact portion arranged so that when the circuit board is mounted on the printing material the second short detection contact portion is the second farthest of the contact portions to the left.

21. The circuit board of claim 20, wherein the memory contact portions are to the left of the short detection contact portion and the second electronic device contact portion and to the right of the second short detection contact portion and the first electronic device contact portion.

22. The circuit board of claim 18, wherein the short detection contact portion is positioned and adapted for detecting a short between the short detection contact portion and at least the second electronic device contact portion, the short detection contact portion being adjacent to the second electronic device contact portion, with no other contact portion therebetween.

23. The circuit board of claim 18, wherein the contact portions are arranged in a first row of contact portions and in a second row of contact portions such that, when the circuit board is mounted on the printing material container and the terminal arrangement is viewed with the printing material container oriented with the exit of the ink supply opening at the bottom, the first row of contact portions is below the second row of contact portions, and

the first electronic device contact portion and the second electronic device contact portion are located at the ends of the first row of contact portions.

24. The circuit board of claim 18, wherein: the contact portions are arranged in a first row of contact portions and in a second row of contact portions, the first row of contact portions and the second row of contact portions extend in a row direction that is, with respect to a condition in which the circuit board is mounted on the printing material container, generally orthogonal to an insertion direction in which the printing material container is mounted into the ink jet printing apparatus,

the first row of contact portions is disposed at a location that is, with respect to a condition in which the circuit board is mounted on the printing material container, further in the insertion direction than the second row of contact portions, and

the first electronic device contact portion and the second electronic device contact portion are located at the ends of the first row of contact portions.

25. An ink supply system connectable to an ink jet printing apparatus, the ink jet printing apparatus having a print head and a plurality of apparatus-side contact forming members, the ink supply system comprising:

- an ink supply structure having an exit opening adapted to supply ink to the printing apparatus;

- a circuit board comprising:

- a memory device adapted to be driven by a memory driving voltage;

- an electronic device adapted to receive a voltage higher than the memory driving voltage; and

- a plurality of terminals having contact portions adapted and positioned to contact corresponding apparatus-side contact forming members so that electrical communication is enabled with the ink jet printing apparatus.

US 8,454,116 B2

33

ratus, the contact portions of the terminals including a plurality of memory contact portions electrically coupled to the memory device, a first electronic device contact portion electrically coupled to the electronic device, a second electronic device contact portion electrically coupled to the electronic device, and a short detection contact portion positioned and arranged to electrically contact a contact forming member that itself is electrically coupled to a short detection circuit of the printing apparatus, wherein: the contact portions are arranged so that, when the terminal arrangement is viewed from the vantage of the contact forming members, with the terminals oriented as if in contact with the contact forming members so that electrical communication is enabled with the ink jet printing apparatus, and with the ink cartridge oriented with the exit opening of the ink supply structure facing downwards, the contact portion farthest to the left is the first electronic device contact portion, the contact portion that is farthest to the right is the second electronic device contact portion, the contact portion that is second farthest to the right is the short detection contact portion, and the memory contact portions are located to the left of the short detection contact portion and to the right of the first electronic device contact portion.

26. The ink supply system of claim 25, wherein the electronic device is adapted to receive a first voltage and output a voltage lower than the first voltage.

34

27. The ink supply system of claim 25, and including a second short detection contact portion arranged so that the second short detection contact portion is the second farthest of the contact portions to the left.

28. The ink supply system of claim 27, wherein the memory contact portions are to the left of the short detection contact portion and the second electronic device contact portion and to the right of the second short detection contact portion and the first electronic device contact portion.

29. The ink supply system of claim 25, wherein the short detection contact portion is positioned and adapted for detecting a short between the short detection contact portion and at least the second electronic device contact portion, the short detection contact portion being adjacent to the second electronic device contact portion, with no other contact portion therebetween.

30. The ink supply system of claim 25, wherein the contact portions are arranged in a first row of contact portions and in a second row of contact portions such that, when the ink supply system is connected to the ink jet printing apparatus, the first row of contact portions is below the second row of contact portions, and the first electronic device contact portion and the second electronic device contact portion are located at the ends of the first row of contact portions.

* * * * *